

KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D  
MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004  
sherry

PAGE  
MSDS NO. 1640<sup>1</sup>

-----  
SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION  
-----

MANUFACTURERS NAME  
W.M. BARR & COMPANY, INC.

ADDRESS  
2105 Channel Ave.  
Memphis, TN 38113 USA

EMERGENCY TELEPHONE #1  
901-775-0100

EMERGENCY CONTACT  
W.M. Barr Technical Services

EMERGENCY INFORMATION

#3E 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.  
SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATION

INVENTORY ITEM #  
GA12272

CHEMICAL FORMULA  
1640

PRODUCT NAME  
AC ACETONE 1 GL

REVISED BY  
W.M. Barr Technical Services

REVISION DATE  
7/30/2003

-----  
SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS  
-----

SUBSTANCE DESCRIPTION	PERCENT	CAS#	CARCINOGENICITY			
			NTP	ACGIH	OSHA	IARC
ACETONE	95-100	67-64-1	N	N	N	N

-----  
SECTION 3. REGULATORY INFORMATION  
-----

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG.AGCY U/M		TWA	STEL	CEIL	SKIN	PEL
	ACGIH	PPM					
ACETONE	OSHA	PPM	500.00 N/E	750.00 N/E	N/E N/E	N N	N/E 1000.00

ADDITIONAL REGULATORY INFO

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)

Ingredients in this product are not listed on California's Prop 65 list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40CFR 372):

SUBSTANCE DESCRIPTION	PERCENT BY WEIGHT (UPPER LIMIT)	CAS#
ACETONE	100	67-64-1

KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D  
MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004  
sherry

PAGE  
MSDS NO. 1640<sup>2</sup>

-----  
SECTION 3. REGULATORY INFORMATION  
(CONTINUED)  
-----

**CLEAN AIR ACT**

This formula contains no known ozone depleting chemicals.

**HAZARD COMMUNICATION STANDARD**

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

\*\*\*\*\*  
The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.  
-----

SECTION 4. HAZARDS IDENTIFICATION  
-----

**INHALATION ACUTE EXPOSURE EFFECTS**

Vapor harmful. May cause dizziness, headache, watering of eyes, irritation of respiratory tract, drowsiness, nausea, and numbness in fingers, arms and legs.

**SKIN CONTACT ACUTE EXPOSURE EFFECTS**

May cause drying of skin, and numbness in fingers and arms. Liquid is absorbed readily.

**EYE CONTACT ACUTE EXPOSURE EFFECTS**

This material is an eye irritant.

**INGESTION ACUTE EXPOSURE EFFECTS**

Harmful if swallowed. May cause dizziness, headache, nausea, and irritation of mouth, throat and stomach.

**CHRONIC EXPOSURE EFFECTS**

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause weakness, fatigue, skin irritation, and numbness in hands and feet.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**PRIMARY ROUTE OF EXPOSURE**

Inhalation, ingestion, and dermal.

-----  
SECTION 5. FIRST AID MEASURES  
-----

**INHALATION**

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

**SKIN CONTACT**

Irritation may result. Immediately wash with soap and water.

**EYE CONTACT**

Immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention.

**INGESTION**

Call your poison control center, hospital emergency room, or physician immediately for instructions.

KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D  
MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004  
sherry

PAGE  
MSDS NO. 1640<sup>3</sup>

-----  
SECTION 5. FIRST AID MEASURES  
(CONTINUED)  
-----

**NOTE TO PHYSICIAN**

This formula is registered with POISINDEX.  
Call your local poison control center for further information.

-----  
SECTION 6. FIRE FIGHTING MEASURES  
-----

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH		1
FLAMMABILITY		3
REACTIVITY		0
OTHER		NA

FLASH METHOD  
TCC

FLASH POINT  
.00 F            -17.77 C

LOWER EXPLOSION LIMIT  
2.60

**GENERAL COMMENTS**

OSHA FLAMMABILITY: Class IB

**EXTINGUISHING METHOD**

Use carbon dioxide, dry powder, or foam.

**FIRE FIGHTING PROCEDURES**

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

**FIRE AND EXPLOSION HAZARDS**

DANGER! EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. VAPORS MAY TRAVEL LONG DISTANCES TO OTHER AREAS AND ROOMS AWAY FROM WORK SITE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

-----  
SECTION 7. ACCIDENTAL RELEASE MEASURES  
-----

**CLEAN-UP**

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D  
MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004  
Shelley

PAGE  
MSDS NO. 1640<sup>4</sup>

-----  
SECTION 7. ACCIDENTAL RELEASE MEASURES  
(CONTINUED)  
-----

**WASTE DISPOSAL**

Dispose in accordance with applicable local, state and federal regulations.

-----  
SECTION 8. HANDLING AND STORAGE  
-----

**STORAGE**

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

**HANDLING**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

-----  
SECTION 9. TRANSPORT INFORMATION  
-----

**TRANSPORTATION**

DOMESTIC: ACETONE, 3, UN1090, PGII

IMDG: ACETONE, 3, UN1090, PGII, FLASHPOINT -4F (-20C), EMS 3-06

IATA (ICAO) Acetone, 3, UN1090, PGII, Flashpoint -4F (-20C)

ERG Code 3H

-----  
SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

**VENTILATION PROTECTION**

USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT. A dust mask does not provide protection against vapors.

**RESPIRATORY PROTECTION**

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

**SKIN PROTECTION**

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

**EYE PROTECTION**

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

**OTHER PROTECTION**

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been

KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D  
MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004  
sherry

PAGE  
MSDS NO. 1640<sup>5</sup>

-----  
SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION  
(CONTINUED)  
-----

contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

-----  
SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES  
-----

VOLATILE %  
100.000  
by weight

BOILING POINT  
GT 133.00 F 56.11 C

VAPOR DENSITY (Air = 1.0)  
Heavier than air

EVAPORATION RATE  
Slower than ether

BULK DENSITY  
6.572  
lbs/gal at 75 F

PH FACTOR  
N/E

PHOTOCHEMICALLY REACTIVE  
NO

MAX V.O.C.  
825 grams per liter (excluding exempt solvents & water)

MAX VAPOR PRESSURE  
(of the V.O.C.) 266mm Hg at 20 degrees C

-----  
SECTION 12. STABILITY AND REACTIVITY  
-----

INCOMPATIBILITIES  
Incompatible with strong oxidizing agents and hydrogen peroxide.

DECOMPOSITION  
Decomposition may produce carbon monoxide and carbon dioxide.

POLYMERIZATION  
Will not occur.

STABILITY  
Stable.

-----  
SECTION 13. ADDITIONAL INFORMATION  
-----

IMPORTANT NOTE

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

KLEAN-STRIP GILLESPIE KWIK DUFFY'S EL PICO P&D  
MATERIAL SAFETY DATA SHEET

DATE PRINTED: 1/27/2004  
sherry

PAGE  
MSDS NO. 1640<sup>6</sup>

-----  
SECTION 13. ADDITIONAL INFORMATION  
(CONTINUED)  
-----

LEGEND:

PPM = parts per million  
MG/M3 = milligrams per cubic meter  
N/E or NE = none established  
GT = greater than  
N/A or NA = not applicable  
TCC = tag closed cup  
TOC = tag open cup  
PMCC = Pensky-Martens closed cup  
IDLH = Immediately Dangerous to Life and Health

\*\*\*END OF MSDS\*\*\*