

1. Product and company identification

Product name	: FAMOWOOD WOOD FILLER SOLVENT
Supplier	: Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621
Material uses	: Not available.
Manufacturer	: Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621
Code	: 730000
Validation date	: 4/12/2010.
Print date	: 4/12/2010.
Responsible name	: Regulatory Compliance
<u>In case of emergency</u>	: CALL INFOTRAC 800-535-5053 001-352-323-3500

2. Hazards identification

Physical state	: Liquid.
Emergency overview	: WARNING ! FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. Flammable liquid. Harmful if swallowed. Irritating to eyes, respiratory system and skin. Keep away from heat, sparks and flame. Do not ingest. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	: Dermal contact. Eye contact. Inhalation.
<u>Potential acute health effects</u>	
Inhalation	: Irritating to respiratory system.
Ingestion	: Harmful if swallowed.
Skin	: Irritating to skin.
Eyes	: Irritating to eyes.
<u>Potential chronic health effects</u>	
Chronic effects	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: lungs, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
<u>Over-exposure signs/symptoms</u>	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: No specific data.

2 . Hazards identification

- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Pre-existing digestive disorders may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3 . Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Methyl Ethyl Ketone	78-93-3	30-60
Acetone	67-64-1	30-60
Solvent Naptha	64742-89-8	10-30

There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

Flammability of the product : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable : Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

Handling : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

7 . Handling and storage

- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Product name

Methyl Ethyl Ketone

Exposure limits

ACGIH TLV (United States, 1/2009). Notes: Substances for which there is a Biological Exposure Index or Indices

STEL: 885 mg/m³ 15 minute(s).

STEL: 300 ppm 15 minute(s).

TWA: 590 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

NIOSH REL (United States, 6/2008).

STEL: 885 mg/m³ 15 minute(s).

STEL: 300 ppm 15 minute(s).

TWA: 590 mg/m³ 10 hour(s).

TWA: 200 ppm 10 hour(s).

OSHA PEL (United States, 11/2006).

TWA: 590 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

OSHA PEL 1989 (United States, 3/1989).

STEL: 885 mg/m³ 15 minute(s).

STEL: 300 ppm 15 minute(s).

TWA: 590 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

Acetone

ACGIH TLV (United States, 1/2009).

STEL: 1782 mg/m³ 15 minute(s).

STEL: 750 ppm 15 minute(s).

TWA: 1188 mg/m³ 8 hour(s).

TWA: 500 ppm 8 hour(s).

NIOSH REL (United States, 6/2008).

TWA: 590 mg/m³ 10 hour(s).

TWA: 250 ppm 10 hour(s).

OSHA PEL (United States, 11/2006).

TWA: 2400 mg/m³ 8 hour(s).

TWA: 1000 ppm 8 hour(s).

OSHA PEL 1989 (United States, 3/1989). Notes: The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.

STEL: 2400 mg/m³ 15 minute(s).

STEL: 1000 ppm 15 minute(s).

TWA: 1800 mg/m³ 8 hour(s).

TWA: 750 ppm 8 hour(s).

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

8 . Exposure controls/personal protection

Personal protection

- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: -17°C (1.4°F) [Tagliabue.]
- Flammable limits** : Lower: 1%
Upper: 12.8%
- Color** : Colorless.
- Odor** : Hydrocarbon.
- Boiling/condensation point** : 56.111°C (133°F)
- Specific gravity** : 0.79
- Vapor pressure** : 24.7 kPa (185 mm Hg)
- Estimated Vapor Density** : >1 [Air = 1]
- VOC %** : 60%
- Evaporation rate** : <1 (Ether (anhydrous). = 1)
- Solubility** : Soluble in the following materials: water.

10 . Stability and reactivity

- Stability** : The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Will not occur.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-------------------------	--------	---------	------	----------

11 . Toxicological information

Methyl Ethyl Ketone	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50	Rat	607 mg/kg	-
	Intraperitoneal			
Acetone	LD50 Oral	Rat	2737 mg/kg	-
	LD50 Intravenous	Rat	5500 mg/kg	-
	LD50 Oral	Rat	5800 mg/kg	-
	LD50 Oral	Rat	5800 mg/kg	-
	LDLo Dermal	Rabbit	20 mL/kg	-
	LDLo	Rat	500 mg/kg	-
	Intraperitoneal			
	TDL0 Oral	Rat	5 mL/kg	-

Carcinogenicity

Conclusion/Summary

IDLH : Not available.

Synergistic products : Not available.

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure	
Methyl Ethyl Ketone	-	Acute EC50 5091000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours	
	-	Acute LC50 >400 ppm Marine water	Fish - Cyprinodon variegatus	96 hours	
	-	Acute LC50 3220000 ug/L Fresh water	Fish - Pimephales promelas	96 hours	
	-	Acute LC50 >520000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours	
	-	Acute LC50 5600000 ug/L Fresh water	Fish - Gambusia affinis	96 hours	
	-	Chronic NOEC <70000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours	
	Acetone	-	Acute LC50 6900 mg/L Fresh water	Daphnia - Daphnia magna	48 hours
		-	Acute LC50 5.54 to 6.33 ml/L Fresh water	Fish - Oncorhynchus mykiss	96 hours
		-	Acute LC50 12100000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
		-	Acute LC50 11000000 to 11300000 ug/L Marine water	Fish - Alburnus alburnus	96 hours
-		Acute LC50 10700000 ug/L Fresh water	Fish - Pimephales promelas	96 hours	
-		Acute LC50 9218000 to 14400000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours	
-		Acute LC50 9100000 to 9482000 ug/L Fresh water	Fish - Pimephales promelas	96 hours	

12 . Ecological information

-	Acute LC50 8800000 ug/L Fresh water	Daphnia - Daphnia pulex	48 hours
-	Acute LC50 8300000 ug/L Fresh water	Fish - Lepomis macrochirus	96 hours
-	Acute LC50 8300000 ug/L Fresh water	Fish - Lepomis macrochirus	96 hours
-	Acute LC50 8120000 to 8760000 ug/L Fresh water	Fish - Pimephales promelas	96 hours
-	Acute LC50 8098000 to 8640000 ug/L Fresh water	Daphnia - Ceriodaphnia dubia	48 hours
-	Acute LC50 7810000 ug/L Fresh water	Daphnia - Daphnia cucullata	48 hours
-	Acute LC50 7460000 ug/L Fresh water	Daphnia - Daphnia cucullata	48 hours
-	Acute LC50 7280000 to 7880000 ug/L Fresh water	Fish - Pimephales promelas	96 hours
-	Acute LC50 6210000 to 7030000 ug/L Fresh water	Fish - Pimephales promelas	96 hours
-	Acute LC50 >100000 ug/L Fresh water	Fish - Pimephales promelas	96 hours
-	Acute LC50 10000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 13300000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 12600000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours

Conclusion/Summary : Not available.

Biodegradability

Conclusion/Summary : Not available.




13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not available.	Consumer commodity	ORM-D	-		Limited quantity Yes. Remarks < . 3 gal Consumer commodity ORM-D
TDG Classification	1993	FLAMMABLE LIQUIDS, N.O.S. (Acetone, Methyl Ethyl Ketone)	3	II		-
IMDG Class	1993	FLAMMABLE LIQUIDS, N.O.S. (Acetone, Methyl Ethyl Ketone)	3	II		Emergency schedules (EmS) F-E, S-E Remarks Limited quantity
IATA-DGR Class	8000	Consumer commodity	9	-		-

PG* : Packing group

15 . Regulatory information

United States inventory (TSCA 8b): All components are listed or exempted.
SARA 311/312 - fire, Acute, Chronic

Canada

WHMIS (Canada)

: Class B-2: Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

: **CEPA Toxic substances:** The following components are listed: Volatile organic compounds

Canadian NPRI: The following components are listed: Methyl ethyl ketone; Volatile organic compounds; Solvent naphtha light aliphatic

Canada inventory

: **Canada inventory:** All components are listed or exempted.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Mexico

Classification

:



EU regulations

Hazard symbol or symbols :



15 . Regulatory information

- Risk phrases** : R11- Highly flammable.
 R36- Irritating to eyes.
 R66- Repeated exposure may cause skin dryness or cracking.
 R67- Vapors may cause drowsiness and dizziness.
- Safety phrases** : S53- Avoid exposure - obtain special instructions before use.
 S2- Keep out of the reach of children.
 S46- If swallowed, seek medical advice immediately and show this container or label.

International regulations

- International lists** : **Australia inventory (AICS)**: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Korea inventory (KECI): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Japan inventory (ENCs): All components are listed or exempted.
Europe inventory: All components are listed or exempted.

16 . Other information

Hazardous Material Information System (U.S.A.) :

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



- Date of printing** : 4/12/2010.
Date of issue : 4/12/2010.
Date of previous issue : No previous validation.
Version : 1

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.