

Safety Data Sheet 70% ISOPROPYL RUBBING ALCOHOL

Section 1. Identification

Product Identifier Synonyms	70% ISOPROPYL RUBBING ALCOHOL MDS098003Z; MDS098010; MDS098011; MDS098012; MDS098013; MDS098016; MDS098017; MSD_SDS0048		
Manufacturer Stock Numbers		98010; MDS098011; MDS09	98012; MDS098013;
Recommended use	N/A		
Uses advised against	N/A		
Manufacturer Contact			
Address	Medline Industries, Inc. 3 Lakes Drive Northfield, IL, 60093 USA		
	Phone	Emergency Phone	Fax
	(800) 633-5463	(800) 424-9300 CHEMTREC	(847) 643-4436
	Website www.Medline.com		

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - DERMAL - Category 5 ACUTE TOXICITY - ORAL - Category 5 EYE DAMAGE/IRRITATION - Category 2B FLAMMABLE LIQUIDS - Category 3 SENSITIZATION - SKIN - Category 1B
Signal Word Pictogram	Warning
Hazard Statements	Causes eye irritation

Page 1 of 6

	Flammable liquid and vapor May be harmful if swallowed May be harmful in contact with skin May cause an allergic skin reaction
Precautionary Statements	
Response	Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. Wash contaminated clothing before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Ground/bond container and receiving equipment. Keep away from heat. Keep container tightly closed. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Wash affected area thoroughly after handling. Wear protective gloves. Wear protective gloves.
Storage	Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with federal, state and local environmental control regulations.
Ingredients of unknown toxicity	N.A.
Hazards not Otherwise Classified	No Data Available

Section 3. Ingredients

CAS	Ingredient Name	Weight %
67-63-0	Isopropyl alcohol	70 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

General Advice:	Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
Eye Contact:	Flush eyes with large amounts of water for at least 15 minutes. Remove contact lenses, if worn. If irritation persists, seek medical attention.
Skin Contact:	Wash with soap and water; if irritation persists, seek medical attention.
Inhalation:	Remove victim to fresh air. Seek medical attention if discomfort continues.
Ingestion:	If swallowed, call a physician immediately. Rinse mouth and throat thoroughly with water. Do not induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	In case of fire, use Water spray, Carbon Dioxide (CO2), Foam, Dry Chemical
Unsuitable Extinguishing Media	N.D.
Unusual Fire and Explosion Hazards:	N.D.
Special Fire Fighting Procedures:	N.D.

Section 6. Accidental Release Measures

 Flammable Small Spill:
 Absorb with an inert dry material and place in an appropriate waste disposal container.

 Flammable Large Spill:
 Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.

Section 7. Handling and Storage

Handling Flammable:Keep away from heat. Keep away from sources of ignition. Ground all equipment
containing material. Do not ingest. Do not breathe gas/ fumes/ vapor/ spray. Avoid
contact with eyes. Wear suitable protective clothing. In case of insufficient
ventilation, wear suitable respiratory equipment. If ingested, seek medical advice
immediately and show the container or the label. Keep away from incompatibles
such as oxidizing agents, acids.Storage Flammable:Store in a segregated and approved area. Keep container in a cool, well-ventilated
area. Keep container tightly closed and sealed until ready for use. Avoid all possible
sources of ignition (spark or flame).

Section 8. Exposure Controls/Personal Protection

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm STEL: 500 ppm	N/A
Goggles, Gloves			
Ventilation: Local exhau	st.		
Air supplied masks or respirator in confined areas			
Protective gloves: Rubb	er Protective gloves: Viny	И.	
Wear chemical safety goggles while handling this product. Do not wear contact lenses. Wear additional eye protection such as face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material.			
: Not expected to be necessary under normal conditions of use. Where exposure cannot be adequately controlled, use appropriate protective clothing or equipment			
Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or usir tobacco. Safety shower and eye wash should be available close to work areas.		ash or using	
	Isopropyl alcohol Goggles, Gloves Ventilation: Local exhaus Air supplied masks or re Protective gloves: Rubbe Wear chemical safety go lenses. Wear additional exists for eye contact wi Not expected to be nece cannot be adequately co Handle in accordance w thoroughly with soap and	Isopropyl alcohol TWA: 200 ppm STEL: 400 ppm Goggles, Gloves Ventilation: Local exhaust. Air supplied masks or respirator in confined area Protective gloves: Rubber Protective gloves: Viny Wear chemical safety goggles while handling this lenses. Wear additional eye protection such as fa exists for eye contact with splashing or spraying I Not expected to be necessary under normal cond cannot be adequately controlled, use appropriate Handle in accordance with good industrial hygien thoroughly with soap and water after handling and	Isopropyl alcohol TWA: 200 ppm STEL: 400 ppm TWA: 400 ppm STEL: 500 ppm Goggles, Gloves Ventilation: Local exhaust. Air supplied masks or respirator in confined areas Protective gloves: Rubber Protective gloves: Vinyl. Wear chemical safety goggles while handling this product. Do not wear co lenses. Wear additional eye protection such as face shield when the possi exists for eye contact with splashing or spraying liquid, or airborne materia Not expected to be necessary under normal conditions of use. Where expo cannot be adequately controlled, use appropriate protective clothing or eq Handle in accordance with good industrial hygiene and safety practice. Wa thoroughly with soap and water after handling and before eating, drinking,

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	Characteristic
	odor
Odor Threshold	N.D.
Solubility	Complete
Partition coefficient Water/n-octanol	N.D
VOC%	N/A
Viscosity	N.D.
Specific Gravity	0.88
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	22°C/72°F
FP Method	TCC
Ph	N.D.
Melting Point	N.A.
Boiling Point	87° C
Boiling Range	N.D.
LEL	2
UEL	12
Evaporation Rate	2.3
Flammability	N.D.
Decomposition Temperature	N.D.
Auto-ignition Temperature	N.D.
Vapor Pressure	33mmHg
Vapor Density	2.07

Section 10. Stability and Reactivity

Stability:	Stable.
Reactivity:	None
Incompatibility (Materials to avoid):	N.D.
Hazardous Decomposition or Byproducts:	Burning may produce Carbon Monoxide, Carbon Dioxide and other hazardous components.
Hazardous Polymerization	N.D.
Conditions to avoid:	Keep away from heat. Sparks. Open flame.

Section 11. Toxicological Information

Acute Toxicity: Eye Contact	Contact may cause temporary moderate irritation
Acute Toxicity: Skin Contact	May cause mild irritation on patients with sensitive skin
Acute Toxicity: Inhalation	N.A.
Acute Toxicity: Ingestion	May be harmful if swallowed
Carcinogenicity:	None known
Chronic Toxicity:	None known

Section 12. Ecological Information

Toxicity:	N.D.
Persistence and	N.D.
degradability:	
Bioaccumulative potential:	N.D.
Mobility in soil:	N.D.
Other adverse effects:	N.D.

Section 13. Disposal

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14. Transport Information

UN Number	1219
UN Proper Shipping Name	Isopropanol, 3
DOT Classification	Hazmat at all levels depending on size of packaging, Excepted or Limited Quantity or Fully Regulated
Packing Group	PG II
Additional Information	IATA OR IMDG - UN1219, Isopropanol,3, PG II

Section 15. Regulatory Information

SARA 311/312:	N.A.
SARA 302:	N.A.
SARA 313:	Isopropyl alcohol.
TSCA:	N.A
CERCLA Hazardous Substance List:	N.A.
Clean Air Act (CAA) Section 112, 112 (r):	N.A.
New Jersey Right to Know Components:	sopropyl Alcohol
Pennsylvania Right to Know Components:	2-PROPANOL.
Rhode Island Right to Know Components:	isopropyl alcohol.

Section 16. Other Information

Revision Date	05/04/2017
Legend	N.A Not Applicable N.E Not Established N.D Not Determined
HMIS (U.S.A.): Health Hazard	1
HMIS (U.S.A.): Flammabil	ity 3
HMIS (U.S.A.): Reactivity	1
National Fire Protection Association (U.S.A): Heal Hazard	1 th
National Fire Protection Association (U.S.A): Flammability	3
National Fire Protection Association (U.S.A): Reactivity	1
Additional Information	The information contained herein is furnished without warranty or legal responsibility of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of

these materials and the safety and health of employees