



GE281 3TG-Tube (0.198LBS-0.090KG) SILICONE SEALANT

250720 Part# GE281 Version: 1.1 '19/2006
CAULK, TUB, GE SILICONE, 2.8-OZ.
2304000 MOMENTIVE PERF. MATERIALS
Buyer: Bernard W. Aubuchon Jr.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: GES Waterford Plant
260 Hudson River Rd
Waterford NY 12188
Revised: 10/19/2006
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use:
Formula: Silicone sealant

HMIS
Flammability: 0 Reactivity: 0 Health: 0 Prot. Equipm.:
NFPA
Flammability: 0 Reactivity: 0 Health: 1 Special Haz.:

2. COMPOSITION/INFORMATION ON INGREDIENTS

Table with 3 columns: PRODUCT COMPOSITION, CAS REG NO., WGT. %. Includes sections A. HAZARDOUS and B. NON-HAZARDOUS with various chemical names and their respective percentages.



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Harmful by inhalation, in contact with skin and if swallowed. May cause skin, eye, and stomach irritation. May cause central nervous system depression. May cause adverse reproductive effects. Adverse reproductive effects reported in animals.

Form: solid

Color: white

Odor: Ammonia

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed. May cause stomach discomfort. May cause central nervous system effects. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Not an anticipated route of exposure.

SKIN

Skin irritation is possible after contact with the uncured product. Uncured product contact will irritate lips, gums and tongue. May cause mild skin irritation. May be absorbed through skin and produce effects as listed under "Ingestion".

INHALATION

Causes mild respiratory tract irritation. Applies in uncured state. May also cause other effects as listed under "Ingestion".

EYES

Eye irritation on contact with the uncured product. May cause mild eye irritation.

MEDICAL CONDITIONS AGGRAVATED

Pre-existing skin or respiratory diseases.

SUBCHRONIC (TARGET ORGAN)

Skin; Central nervous system

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Inhalation; dermal; Eyes; Oral.

FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. Get medical attention if irritation persists.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

None known.

5 FIRE-FIGHTING MEASURES

FLASH POINT:

METHOD:

not applicable not applicable

IGNITION TEMPERATURE:

Unknown

FLAMMABLE LIMITS IN AIR - LOWER (%):

Unknown

FLAMMABLE LIMITS IN AIR - UPPER (%):

Unknown

SENSITIVITY TO MECHANICAL IMPACT:

No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6 ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

7. HANDLING AND STORAGE

STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Keep away from children. Keep container tightly closed. Use mechanical ventilation to stay below TLV of 25 ppm ammonia. Store away from heat, sources of ignition, and incompatibles.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).

PROTECTIVE GLOVES

Cloth gloves.

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	not applicable
VAPOR PRESSURE (20 C) (MM HG):	not applicable
VAPOR DENSITY (AIR=1):	
FREEZING POINT:	not applicable
MELTING POINT:	not applicable
PHYSICAL STATE:	solid



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

ODOR:	Ammonia
COLOR:	white
EVAPORATION RATE (BUTYL ACETATE=1):	
SPECIFIC GRAVITY (WATER=1):	1.03
DENSITY:	1.03 g/cm3
ACID / ALKALINITY (MEQ/G):	Unknown
pH:	not applicable
VOLATILE ORGANIC CONTENT (VOL):	not applicable
SOLUBILITY IN WATER (20 C):	insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	PARTIAL IN TOLUENE
VOC EXCL. H2O & EXEMPTS (G/L):	27.00

10. STABILITY AND REACTIVITY

STABILITY
Stable

HAZARDOUS POLYMERIZATION
Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS
Methanol; Carbon dioxide (CO2); Carbon monoxide; Ammonia; Silicon dioxide.

INCOMPATIBILITY (MATERIALS TO AVOID)
None known.

CONDITIONS TO AVOID
None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL
Remarks: Unknown

ACUTE DERMAL
Remarks: Unknown

ACUTE INHALATION
Remarks: Unknown

OTHER
Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

SENSITIZATION



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

SKIN IRRITATION

EYE IRRITATION

MUTAGENICITY
Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGY
no data available

CHEMICAL FATE
no data available

DISTRIBUTION

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD
Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

TSCA list	y (positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)
Canada NDSL Inventory	n (Negative listing)
EU list of existing chemical substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Canada DSL Inventory	y (positive listing)



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

Korea Existing Chemicals Inventory (KECI) y (positive listing)
China Inventory of Existing Chemical Substances y (positive listing)

For inventories that are marked as quantity restricted or special cases, please contact GE.

US Regulatory Information

CERCLA
PRODUCT COMPOSITION Chemical CERCLA Reportable Quantity

CLEAN AIR ACT

CLEAN WATER ACT

SARA SECTION 302

SARA (311,312) HAZARD CLASS

SARA (313) CHEMICALS

Canadian Regulatory Information

WHMIS HAZARD CLASS
D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS: 3214.10.00.10 Mastic based on rubber

ECCN: EAR99

CALIFORNIA PROPOSITION 65
None.

16. OTHER INFORMATION

OTHER

C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product. TSCA inventory status



**GE281 3TG-Tube (0.198LBS-0.090KG)
SILICONE SEALANT**

not required under 40 CFR part 720.30 (h-2). These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.