MATERIAL SAFETY DATA SHEET

Share Corporation P.O. Box 245013 Milwaukee, WI 53224

GENERAL INFORMATION NUMBER: 414-355-4000 EMERGENCY TELEPHONE NUMBER: (800) 776-7192

CHEMTREC: (800) 424-9300



REVISION DATE: April 20, 2009 DATE OF ISSUE: April 20, 2009

Y: Yes

N: No

I - Product Identification

Gas Line Anti-Freeze

PRODUCT CODE: 0650

CHEMICAL FORMULATION: Alcohol based solution.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 3 REACTIVITY: 0 HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients Values reported as TWA unless noted. APPROX **OSHA ACGIH** EPA 40 CFR: **SUBSTANCE** PEL TLV CAS# % 302 355 372 > 90.0Y 67-56-1 Methanol 200 ppm 200 ppm N

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit

N/A: Not Applicable N/D: Not Determined N/E: Not Established **302**: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).

372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): 148.5 SPECIFIC GRAVITY (WATER = 1): 0.81 VAPOR PRESSURE (mm Hg): 100 at 21.2°C VOC CONTENT (% by weight): N/D

VAPOR DENSITY (AIR = 1): $1.1 @ 20^{\circ}C$ **EVAPORATION RATE (WATER = 1):** > 1.0

SOLUBILITY IN WATER: Soluble **pH:** N/A

APPEARANCE AND ODOR: Clear, colorless liquid; alcohol odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 52 (TEST METHOD): Open Cup

FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: 36 LOWER: 6

EXTINGUISHING MEDIA: Water spray, water fog, alcohol resistant foam, dry chemical, CO₂.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus. Evacuate area and fight from a maximum distance or use unmanned hose holders or monitor nozzles. Heat may generate flammable or explosive vapors; disperse with water spray or cover pooling liquid with foam. Containers can build up pressure if exposed to heat; cool with flooding quantities of water until well after fire is out.

UNUSUAL FIRE AND EXPLOSION HAZARD: Methanol is TOXIC. Avoid all exposure, especially ingestion. Product can release vapors that form flammable mixtures at temperatures at or above the flashpoint. Vapors may travel long distances along the ground before reaching a source of ignition and flashing back Material can burn with little or no visible flame. Containers may explode in heat of fire.

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizing agents, aluminum, zinc, or metals that displace hydrogen, rubber and rubber based coatings, chromic anhydride, lead perchlorate and perchloric acid.

CONDITIONS TO AVOID: Excess heat, sparks and open flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon and toxic vapors such as formaldehyde and formic acid.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: X EYE CONTACT: X SKIN CONTACT: X INGESTION: X INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None. EFFECTS OF OVEREXPOSURE

IF IN EYES: Irritating, can cause conjunctivitis and or corneal opacity. Will injure eye tissue if not removed promptly.

IF ON SKIN: Irritation and dermatitis, with prolonged or repeated exposure. May cause significant toxicity.

IF SWALLOWED: Small amounts of the liquid aspirated into the respiratory system during ingestion, or from vomiting, may cause bronchiopneumonia or pulmonary edema. Small doses (1 to 2 ounces) can cause metabolic acidosis leading to optic nerve damage ranging from diminished visual capacity to complete blindness, and death.

IF INHALED: Irritation to respiratory system, drowsiness, dizziness, headache.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Flush with water for at least 15 minutes while removing any contaminated clothing. If irritation persists, obtain medical attention. Launder clothing separately before reuse.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting unless told to do so by a physician or poison control center. Keep person at rest.

IF INHALED: Remove person to fresh air. Administer artificial respiration if breathing has stopped. Obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal. WASTE DISPOSAL METHOD: Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION LOCAL: Recommended MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant. **EYE PROTECTION:** Safety glasses or goggles.

OTHER PROTECTIVE EQUIPMENT: Protective clothing.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information

DOT ID NUMBER: UN1230 **DOT PROPER SHIPPING NAME:** Methanol

DOT CLASS: 3 DOT PACKING GROUP: II

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: June 2, 2009 Prepared by: Technical Dept DATE OF ISSUE: June 2, 2009

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.