

# SAFETY DATA SHEET

Creation Date 27-Apr-2009	Revision Date 18-Jan-2018	Revision Number 6
	1. Identification	
Product Name	Methanol	
Cat No. :	A412-1; A412-4; A412-4LC; A412-20; A412- A412-200LC; A412-500; A412CU-1300; A41 A412FB-19; A412FB-50; A412FB-115; A412 A412POPB-200; A412RB50; A412RB-115; A412RS-28; A412RS-50; A412RS-115; A41 XXA412ETU200LI; NC1282211; XXA412ET	I2P-4; A412SK-4; 2FB-200; A412POP-19; A412RB-200; A412RS-19; 2RS-200; A412SS-115;
CAS-No Synonyms	67-56-1 Methyl alcohol	
Recommended Use Uses advised against	Laboratory chemicals. Not for food, drug, pesticide or biocidal product use	
Details of the supplier of the sa	fety data sheet	

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

## **Emergency Telephone Number**

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

## 2. Hazard(s) identification

Classification This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Optic nerve.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen, Blood.	

## Label Elements

Signal Word Danger

## Hazard Statements

Highly flammable liquid and vapor

Toxic if swallowed Toxic in contact with skin Toxic if inhaled Causes damage to organs Causes damage to organs through prolonged or repeated exposure



#### Precautionary Statements Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool Response IF exposed: Call a POISON CENTER or doctor/physician Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician Skin Call a POISON CENTER or doctor/physician if you feel unwell Wash contaminated clothing before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Rinse mouth Fire In case of fire: Use CO2, dry chemical, or foam for extinction Storage Store locked up Store in a well-ventilated place. Keep container tightly closed Disposal

Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC)

## Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. **WARNING.** Reproductive Harm - https://www.p65warnings.ca.gov/.

## 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methyl alcohol	67-56-1	>95

4. First-aid measures		
General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.	
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.	
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.	
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.	
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.	
Most important symptoms and effects Notes to Physician	Breathing difficulties. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting Treat symptomatically	
	5. Fire-fighting measures	
Suitable Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.	
Unsuitable Extinguishing Media	Water may be ineffective	
Flash Point	12 °C / 53.6 °F	
Method -	No information available	
Autoignition Temperature	455 °C / 851 °F	
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	31.00 vol % 6.0 vol % t No information available No information available	

## Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

## **Hazardous Combustion Products**

Carbon monoxide (CO) Formaldehyde

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u>	Health 1	Flammability 3	<b>Instability</b> 0	Physical hazards N/A
6. Accidental release measures				
Personal F	Precautions	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.		
Environme	ental Precautions	Should not be released into the environment. See Section 12 for additional ecological		

#### information.

Methods for Containment and CleanSoak up with inert absorbent material. Keep in suitable, closed containers for disposal.UpRemove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

	7. Handling and storage
Handling	Wear personal protective equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

# 8. Exposure controls / personal protection

## Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm	TWA: 260 mg/m <sup>3</sup>
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>	STEL: 250 ppm
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm	STEL: 310 mg/m <sup>3</sup>
		Skin	STEL: 325 mg/m <sup>3</sup>	_
		TWA: 200 ppm	_	
		TWA: 260 mg/m <sup>3</sup>		

#### <u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

Physical State Liquid   Appearance Colorless   Address Alashal like	9. Physical and chemical properties	
	Physical State	Liquid
	Appearance	Colorless
Alcohorike	Odor	Alcohol-like
Odor Threshold No information available	Odor Threshold	No information available
pH Not applicable	рН	Not applicable

Melting Point/Range Boiling Point/Range Flash Point Evaporation Rate Flammability (solid,gas) Flammability or explosive limits	-98 °C / -144.4 °F 64.7 °C / 148.5 °F @ 760 mmHg 12 °C / 53.6 °F 5.2 (ether = 1) Not applicable
Upper	31.00 vol %
Lower	6.0 vol %
Vapor Pressure	128 hPa @ 20 °C
Vapor Density	1.11
Specific Gravity	0.791
Solubility	Miscible with water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	455 °C / 851 °F
Decomposition Temperature	No information available
Viscosity	0.55 cP at 20 °C
Molecular Formula	C H4 O
Molecular Weight	32.04
VOC Content(%)	100
Surface tension	0.02255 N/m @ 20°C

# 10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases, Metals, Peroxides
Hazardous Decomposition Product	<b>s</b> Carbon monoxide (CO), Formaldehyde
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

## 11. Toxicological information

## Acute Toxicity

# Product Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg ( Rat )	Calc. ATE 60 mg/kg LD50 = 17100 mg/kg(Rabbit)	Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L ( Rat ) 4 h
Toxicologically Synergistic Products Delayed and immediate effects	Carbon tetrachloride s as well as chronic effects fron	n short and long-term exposur	<u>e</u>
Irritation	May cause skin and eye in	ritation	
Constitution	No information available		
Sensitization			

Methyl alcohol     67-56-1     Not listed     Not listed     Not listed     Not listed     Not listed	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
	Methyl alcohol	67-56-1	Not listed				

Mutagenic Effects	No information available
Reproductive Effects	No information available.
Developmental Effects	Component substance is listed on California Proposition 65 as a developmental hazard.
Teratogenicity	No information available.
STOT - single exposure STOT - repeated exposure	Optic nerve Kidney Liver spleen Blood
Aspiration hazard	No information available
Symptoms / effects,both acute and delayed	May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

## Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Persistence and Degrada	ability Persistence	is unlikely based on inform	ation available.	
Bioaccumulation/ Accum	nulation No informati	on available.		

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl alcohol	-0.74

## 13. Disposal considerations

Waste Disposal Methods

Should not be released into the environment.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

14. Transport information								
DOT	ΟΤ							
UN-No	UN1230							
Proper Shipping Name	METHANOL							
Hazard Class	3							
Packing Group	11							
TDG								
UN-No	UN1230							
Proper Shipping Name	METHANOL							
Hazard Class	3							
Subsidiary Hazard Class	6.1							
Packing Group	11							
IATA								
UN-No	UN1230							
Proper Shipping Name	METHANOL							
Hazard Class	3							

Subsidiary Hazard Class Packing Group	6.1 II
IMDG/IMO	
UN-No	UN1230
Proper Shipping Name	METHANOL
Hazard Class	3
Subsidiary Hazard Class	6.1
Packing Group	II
	15 Doc

## 15. Regulatory information

## International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Methyl alcohol	Х	Х	-	200-659-6	-		Х	Х	Х	Х	Х

Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

## U.S. Federal Regulations

TSCA 12(b) Not applicable

**SARA 313** 

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Not applicable

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	Х		-

**OSHA** Occupational Safety and Health Administration Not applicable

## CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Su	bstances RQs	CERCLA EHS RQs
Methyl alcohol	500	0 lb	-
Colifornia Dronosition 65	This product contains the following	a proposition 65 ob	omicolo

California Proposition 05		

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	X	X	X	X	X

## **U.S. Department of Transportation**

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

#### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

## Other International Regulations

## Mexico - Grade

Serious risk, Grade 3

	16. Other information
Prepared By	Regulatory Affairs
	Thermo Fisher Scientific
	Email: EMSDS.RA@thermofisher.com
Creation Date	27-Apr-2009
Revision Date	18-Jan-2018
Print Date	18-Jan-2018
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of SDS**