



# Safety Data Sheet

## Spartan Chemical Company, Inc.

Revision Date: 07-Aug-2015

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier**

**Product Name:** CONCRETE SEAL  
**Product Number:** 2977  
**Recommended Use:** Concrete seal  
**Uses Advised Against:** For Industrial and Institutional Use Only

**Manufacturer/Supplier:** Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, Ohio 43537 USA  
800-537-8990 (Business hours)  
[www.spartanchemical.com](http://www.spartanchemical.com)

**24 Hour Emergency Phone Numbers:**

**Medical Emergency/Information:** 888-314-6171  
**Transportation/Spill/Leak:** CHEMTREC 800-424-9300

### 2. HAZARDS IDENTIFICATION

**GHS Classification**

Acute Toxicity - Oral: Category 4  
Skin Corrosion/Irritation: Category 2  
Serious Eye Damage/Eye Irritation: Category 2A  
Carcinogenicity: Category 1B  
Reproductive Toxicity: Category 2  
Specific Target Organ Toxicity (Single Exposure): Category 3  
Aspiration Toxicity: Category 1  
Flammable Liquids: Category 3

**GHS Label Elements**

**Signal Word:**

**Symbols:**

**Danger**



**Hazard Statements:**

Harmful if swallowed.  
Causes skin irritation.  
Causes serious eye irritation  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor.

**Precautionary Statements:**

<b>Prevention:</b>	Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wear eye / face protection Wear protective gloves Wash hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground container and receiving equipment. Use explosion-proof electrical equipment. Use only non-sparking tools Take precautionary measures against static discharge
<b>Response:</b>	<b>If exposed or concerned: Get medical attention.</b>
<b>-Eyes</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>-Skin</b>	IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.
<b>-Inhalation:</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell
<b>-Ingestion:</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting.
<b>-Specific Treatment:</b>	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
<b>Fire:</b>	In case of fire: Use CO2, dry chemical, or foam for extinction
<b>Storage:</b>	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
<b>Disposal:</b>	Dispose of contents and container in accordance with local, state and federal regulations.
<b>Hazards Not Otherwise Classified:</b>	Not Applicable
<b>Other Information:</b>	<ul style="list-style-type: none"> <li>• Contains petroleum distillates. Possible aspiration hazard.</li> <li>• Keep out of reach of children.</li> </ul>

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
aromatic hydrocarbon	64742-95-6	30-60
trimethylbenzenes	25551-13-7	10-30
acrylic polymer	PROPRIETARY	10-30
ethylmethylbenzenes	25550-14-5	5-10
propylbenzene	103-65-1	1-5
xylene	1330-20-7	1-5
cumene	98-82-8	1-5
ethylbenzene	100-41-4	0.1-1
toluene	108-88-3	0.1-1
naphthalene	91-20-3	0.1-1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

<b>-Eye Contact:</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>-Skin Contact:</b>	Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical attention.
<b>-Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.

**-Ingestion:** IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Do NOT induce vomiting.  
**Note to Physicians:** Contains petroleum distillates. Possible aspiration hazard.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:** Carbon dioxide, Dry chemical, Alcohol resistant foam  
**Specific Hazards Arising from the Chemical:** flammable. Vapors may travel to source of ignition and flash back.  
**Hazardous Combustion Products:** May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.  
**Protective Equipment and Precautions for Firefighters:** Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Remove all sources of ignition. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.  
**Environmental Precautions:** Do not rinse spill onto the ground, into storm sewers or bodies of water.  
**Methods for Clean-Up:** Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

## 7. HANDLING AND STORAGE

**Advice on Safe Handling:** Handle in accordance with good industrial hygiene and safety practice. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Never pierce, drill, grind, cut, saw or weld any empty container.  
**Storage Conditions:** Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
trimethylbenzenes 25551-13-7	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m <sup>3</sup>	-
xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>
ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
naphthalene 91-20-3	STEL: 15 ppm TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m <sup>3</sup> (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m <sup>3</sup>	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>

**Engineering Controls:**

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

**Personal Protective Equipment****Eye/Face Protection:**

Wear splash goggles.

**Skin and Body Protection:**

Wear solvent-resistant gloves. The use of other protective equipment such as solvent-resistant boots should be considered in order to prevent or minimize contact with this product.

**Respiratory Protection:**

Ensure adequate ventilation, especially in confined areas

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

Respirator selection must be made by a technically qualified person who is familiar with the specific work conditions.

**General Hygiene Considerations:**

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance/Physical State:</b>	Liquid
<b>Color:</b>	Clear
<b>Odor:</b>	aromatic solvent
<b>pH:</b>	Not Applicable
<b>Melting Point / Freezing Point:</b>	No information available.
<b>Boiling Point / Boiling Range:</b>	155 °C / 311 °F
<b>Flash Point:</b>	42 °C / 108 °F ASTM D56
<b>Evaporation Rate:</b>	< 1 (Butyl acetate = 1)
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper Flammability Limit:</b>	No information available.
<b>Lower Flammability Limit:</b>	No information available.
<b>Vapor Pressure:</b>	No information available.
<b>Vapor Density:</b>	No information available.
<b>Specific Gravity:</b>	0.90
<b>Solubility(ies):</b>	Insoluble in water
<b>Partition Coefficient:</b>	No information available.
<b>Autoignition Temperature:</b>	No information available.
<b>Decomposition Temperature:</b>	No information available.
<b>Viscosity:</b>	No information available.

## 10. STABILITY AND REACTIVITY

**Reactivity:**

This material is considered to be non-reactive under normal conditions of use.

**Chemical Stability:**

Stable under normal conditions.

**Possibility of Hazardous Reactions:**

Not expected to occur with normal handling and storage.

**Conditions to Avoid:**

Heat, flames and sparks.

**Incompatible Materials:**

Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products:** May include carbon monoxide, carbon dioxide (CO<sub>2</sub>) and other toxic gases or vapors.

## 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Eyes, Skin, Ingestion, Inhalation.  
**Symptoms of Exposure:**  
**-Eye Contact:** Pain, redness, swelling of the conjunctiva and blurred vision.  
**-Skin Contact:** Pain, redness and cracking of the skin. May be absorbed through the skin in harmful amounts  
**-Inhalation:** May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Nasal discomfort and coughing.  
**-Ingestion:** Pain, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

### Immediate, Delayed, Chronic Effects

**Product Information:** Data not available or insufficient for classification.

**Target Organ Effects:** Central nervous system. -Eyes. Respiratory System. -Skin.

### Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 1910 mg/kg

ATEmix (dermal): 2220 mg/kg

ATEmix (inhalation-dust/mist): 59 mg/l

### Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
aromatic hydrocarbon 64742-95-6	Not Available	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
trimethylbenzenes 25551-13-7	= 8970 mg/kg ( Rat )	Not Available	Not Available
propylbenzene 103-65-1	= 6040 mg/kg ( Rat )	Not Available	Not Available
xylene 1330-20-7	= 4300 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 47635 mg/L ( Rat ) 4 h
cumene 98-82-8	= 1400 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h
ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15354 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
toluene 108-88-3	= 636 mg/kg ( Rat )	= 8390 mg/kg ( Rabbit ) = 12124 mg/kg ( Rat )	= 12.5 mg/L ( Rat ) 4 h > 26700 ppm ( Rat ) 1 h
naphthalene 91-20-3	= 490 mg/kg ( Rat )	> 2500 mg/kg ( Rat ) > 20 g/kg ( Rabbit )	> 340 mg/m <sup>3</sup> ( Rat ) 1 h

**Carcinogenicity:** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
cumene 98-82-8	Not Listed	Group 2B	Not Listed	Listed
ethylbenzene 100-41-4	Not Listed	Group 2B	Not Listed	Not Listed
naphthalene 91-20-3	Not Listed	Group 2B	Reasonably Anticipated	Listed

*IARC (International Agency for Research on Cancer): Group 2B - Possibly Carcinogenic to Humans*

*NTP (National Toxicology Program): Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
aromatic hydrocarbon 64742-95-6	Not Available	9.22: 96 h Oncorhynchus mykiss mg/L LC50	Not Available	6.14: 48 h Daphnia magna mg/L EC50

trimethylbenzenes 25551-13-7	Not Available	7.72: 96 h Pimephales promelas mg/L LC50 flow-through	Not Available	Not Available
xylene 1330-20-7	Not Available	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	Not Available	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	Not Available	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static
ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	Not Available	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	Not Available	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50

naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	Not Available	2.16: 48 h Daphnia magna mg/L LC50 1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static
------------------------	---	--	---------------	---

**Persistence and Degradability:** No information available.

**Bioaccumulation:** No information available.

**Other Adverse Effects:** No information available.

### 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:** Dispose of in accordance with federal, state and local regulations.

**Contaminated Packaging:** Dispose of in accordance with federal, state and local regulations.

**US EPA Waste Number:** D001, U019 U055 U165 U220 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
xylene 1330-20-7		Included in waste stream: F039		U239
cumene 98-82-8				U055
ethylbenzene 100-41-4		Included in waste stream: F039		
toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
------------------------	--	--	--	--

**14. TRANSPORT INFORMATION**

**DOT:** Regulated  
**UN/ID No:** UN1993  
**Proper Shipping Name:** Flammable liquids, n.o.s., (contains petroleum distillates)  
**Hazard Class:** 3  
**Packing Group:** III  
**Special Provisions:** Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

**IMDG:**  
**UN/ID No:** UN1993  
**Proper Shipping Name:** Flammable liquids, n.o.s., (contains petroleum distillates)  
**Hazard Class:** 3  
**Packing Group:** III

**15. REGULATORY INFORMATION**

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory)  
 All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SARA 313**  
 This product contains the following listed substances:

- xylene**  
CAS No 1330-20-7
- cumene**  
CAS No 98-82-8
- ethylbenzene**  
CAS No 100-41-4
- naphthalene**  
CAS No 91-20-3

**SARA 311/312 Hazard Categories**

**Acute Health Hazard:** Yes  
**Chronic Health Hazard:** Yes  
**Fire Hazard:** Yes  
**Sudden release of pressure hazard:** No  
**Reactive Hazard:** No

**California Proposition 65**

This product is not subject to warning requirements under California Proposition 65.

**16. OTHER INFORMATION**



---

<u>NFPA</u>	Health Hazards: 2	Flammability: 2	Instability: 0	Special: N/A
<u>HMIS</u>	Health Hazards: 2*	Flammability: 2	Physical Hazards: 0	

Revision Date: 07-Aug-2015  
Reasons for Revision: Section 14 and 15

**Disclaimer:**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**