

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

**1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

Ashland P.O. Box 2219 Columbus, OH 43216	Regulatory Information Number Telephone Emergency telephone number	1-800-325-3751 614-790-3333 1-800-ASHLAND (1-800-274-5263)
Product name	PARTS PLUS ® SAE 10W-30 SYNTHETIC MOTOR OIL	
Product code	PP3502	
Product Use Description	No data	

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: liquid, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

**Potential Health Effects**

**Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye contact**

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

**Skin contact**

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

**Inhalation**

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

**Target Organs**

No data

**Carcinogenicity**

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

**Reproductive hazard**

There are no data available for assessing risk to the fetus from maternal exposure to this material.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Hazardous Components</b>	<b>CAS-No.</b>	<b>Concentration</b>
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	>=90-<=100%
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=1.5-<5%

**4. FIRST AID MEASURES**

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

### **Eyes**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

### **Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

### **Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### **Inhalation**

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

### **Notes to physician**

**Hazards:** Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

**Treatment:** No information available.

## **5. FIRE-FIGHTING MEASURES**

### **Suitable extinguishing media**

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Water spray

### **Hazardous combustion products**

carbon dioxide and carbon monoxide, Hydrocarbons

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

**Precautions for fire-fighting**

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

**Environmental precautions**

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

**Methods for cleaning up**

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

**Other information**

Comply with all applicable federal, state, and local regulations.

**7. HANDLING AND STORAGE**

**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

**Storage**

Store in a cool, dry, ventilated area.

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Exposure Guidelines**

---

**HYDROTREATED PARAFFINIC DISTILLATE,  
DEWAXED**

---

#### **General advice**

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

#### **Exposure controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### **Eye protection**

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

#### **Skin and body protection**

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

#### **Respiratory protection**

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	liquid
<b>Form</b>	no data available
<b>Colour</b>	amber
<b>Odour</b>	no data available
<b>Boiling point/boiling range</b>	662 °F / 350 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas
<b>Melting point/range</b>	no data available
<b>Sublimation point</b>	no data available
<b>pH</b>	no data available
<b>Flash point</b>	(>)390 °F / 199 °C Cleveland open cup
<b>Ignition temperature</b>	no data available
<b>Evaporation rate</b>	no data available
<b>Lower explosion limit/Upper explosion limit</b>	no data available
<b>Particle size</b>	no data available
<b>Vapour pressure</b>	0.133 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
<b>Relative vapour density</b>	no data available
<b>Density</b>	0.8527 g/cm <sup>3</sup> @ 60.01 °F / 15.56 °C 7.1 lb/gal @ 60.00 °F / 15.56 °C
<b>Bulk density</b>	No data
<b>Water solubility</b>	negligible
<b>Solubility</b>	no data available
<b>Partition coefficient: n-octanol/water</b>	no data available
<b>log Pow</b>	no data available
<b>Autoignition temperature</b>	no data available
<b>Viscosity, dynamic</b>	no data available
<b>Viscosity, kinematic</b>	10.7 mm <sup>2</sup> /s
<b>Solids in Solution</b>	no data available
<b>Decomposition temperature</b>	no data available
<b>Burning number</b>	no data available
<b>Dust explosion constant</b>	no data available
<b>Minimum ignition energy</b>	no data available

## 10. STABILITY AND REACTIVITY

**Stability**

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

Stable.

**Conditions to avoid**

None known.

**Incompatible products**

Strong oxidizing agents

**Hazardous decomposition products**

carbon dioxide and carbon monoxide, Hydrocarbons

**Hazardous reactions**

Product will not undergo hazardous polymerization.

**Thermal decomposition**

No data

**11. TOXICOLOGICAL INFORMATION**

**Acute oral toxicity**

HYDROTREATED HEAVY PARAFFINIC BASE OIL : LD 50 Rat: > 15 g/kg

HEAVY PARAFFINIC DISTILLATE : LD 50 Rat: > 15 g/kg

**Acute inhalation toxicity**

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

**Acute dermal toxicity**

HYDROTREATED HEAVY PARAFFINIC BASE OIL : LD 50  
Rabbit:  
> 5 g/kg

HEAVY PARAFFINIC DISTILLATE : LD 50  
Rabbit:  
> 5 g/kg

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

## 12. ECOLOGICAL INFORMATION

### Biodegradability

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

### Bioaccumulation

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

### Ecotoxicity effects

#### Toxicity to fish

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

#### Toxicity to daphnia and other aquatic invertebrates.

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

#### Toxicity to algae

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

#### Toxicity to bacteria

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

#### Biochemical Oxygen Demand (BOD)

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available



PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

**Chemical Oxygen Demand (COD)**

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

**Additional ecological information**

HYDROTREATED HEAVY PARAFFINIC BASE OIL : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

**14. TRANSPORT INFORMATION**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

Not dangerous goods

**U.S. DOT - RAIL**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TRANSPORT CANADA - ROAD**

Not dangerous goods

**TRANSPORT CANADA - RAIL**

PARTS PLUS ® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

Not dangerous goods

**TRANSPORT CANADA - INLAND WATERWAYS**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**15. REGULATORY INFORMATION**

**California Prop. 65**

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**SARA Hazard Classification**

No SARA Hazards

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**New Jersey RTK Label Information**

HYDROTREATED HEAVY PARAFFINIC BASE OIL

64742-54-7

PARTS PLUS® SAE 10W-30 SYNTHETIC  
MOTOR OIL  
PP3502

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED  
HEAVY PARAFFINIC DISTILLATE 64742-54-7  
POLYOLEFIN AMIDE ALKENEAMINE  
LUBRICANT ADDITIVE

**Pennsylvania RTK Label Information**

HYDROTREATED HEAVY PARAFFINIC BASE OIL 64742-54-7  
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED  
HEAVY PARAFFINIC DISTILLATE 64742-54-7

**Notification status**

US. Toxic Substances Control Act y (positive listing)  
Canada. Canadian Environmental Protection Act (CEPA). y (positive listing)  
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)  
Australia. Industrial Chemical (Notification and Assessment) y (positive listing)  
Act  
New Zealand. Inventory of Chemicals (NZIoC), as published n (Negative listing)  
by ERMA New Zealand  
Japan. Kashin-Hou Law List n (Negative listing)  
Korea. Toxic Chemical Control Law (TCCL) List y (positive listing)  
Philippines. The Toxic Substances and Hazardous and Nuclear y (positive listing)  
Waste Control Act  
China. Inventory of Existing Chemical Substances q (quantity restricted)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).