Version 1.0	Revision Date 04/24/2015	Print Date 05/29/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	Hillyard Quick & Clean Vanilla Air Freshener Odor and Smoke Neutralizer
Material number	:	A00207
Manufacturer or supplier's	detai	ils
Company	:	Hillyard Industries
Address	:	302 North 4 th Street Joseph, MO 64502
Telephone	:	816-233-1321 ext 8285
Emergency telephone n	umb	ers
For SDS Information		: 816-233-1321 ext 8285
For a Medical Emergency		:
For a Transportation Emergency		: CHEMTREC 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols	:	Category 1
Gases under pressure	:	Liquefied gas
Eye irritation	:	Category 2A
Specific target organ toxicity -	:	Category 3 (Central nervous system)
single exposure		

GHS Label element

Hazard pictograms

Signal word



Hazard statements: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.
 P261 Avaid breathing dust(fume/space/mist/veneum/space)

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

ersion 1.0	Revision Date 04/24/2015	Print Date 05/29/2015
Potential Health Effects	Revision Date 04/24/2015Print Date 05/29/2015P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear eye protection/ face protection.Response:P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention.Storage: P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place.Disposal: P501 Dispose of contents/container in accordance with local regulation.	
Carcinogenicity:		
IARC	No component of this product prese equal to 0.1% is identified as probat human carcinogen by IARC.	
ACGIH	No component of this product prese equal to 0.1% is identified as a carci carcinogen by ACGIH.	
OSHA	No component of this product prese equal to 0.1% is identified as a carci carcinogen by OSHA.	
NTP	No component of this product prese equal to 0.1% is identified as a know by NTP.	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
Trade Secret	Not Assigned	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area. Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Version 1.0	Revision Date 04/24/2015	Print Date 05/29/2015
If inhaled	: Remove to fresh air immediately. G immediately.	et medical attention
In case of skin contact	 Wash off immediately with plenty of minutes. Take off contaminated clothing and Get medical attention if irritation de Wash contaminated clothing before 	l shoes immediately. velops and persists.
In case of eye contact	 In case of contact, immediately flus for at least 15 minutes. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a space. 	
If swallowed	: DO NOT induce vomiting unless dir physician or poison control center. Never give anything by mouth to ar If symptoms persist, call a physicial	n unconscious person.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO2) Dry chemical Water spray jet Alcohol-resistant foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

: Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive
concentrations. Vapours can accumulate in low areas.

Version 1.0	Revision Date 04/24/2015	Print Date 05/29/2015
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. 	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent mate acid binder, universal binder, sawo Sweep up or vacuum up spillage a container for disposal.	lust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Wear cold-insulating gloves/face shield/eye protection. Always replace cap after use.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0

Version 1.0	Revision	Date 04/24/2015	Print D	Date 05/29/2015
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	50 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Personal protective equipment

Respiratory protection :	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrat that exposures are within recommended exposure guideline	
Hand protection		
•	The suitability for a specific workplace should be discussed with the producers of the protective gloves.	
Eye protection :	Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses	
Skin and body protection :	impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.	
Hygiene measures :	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: characteristic

ersion 1.0	Revision Date 04/24/2015	Print Date 05/29/2015
Odour Threshold	: no data available	
рН	: no data available	
Melting point/freezing point	: no data available	
Boiling point	: no data available	
Flash point	: not applicable	
Evaporation rate	: no data available	
Flammability (solid, gas)	: Extremely flammable aerosol.	
Upper explosion limit	: no data available	
Lower explosion limit	: no data available	
Vapour pressure	: 3,447 - 4,136 hPa	
Relative vapour density	: no data available	
Density	: no data available	
Solubility(ies)		
Water solubility	: soluble	
Partition coefficient: n- octanol/water	: no data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: no data available	
Viscosity		
Viscosity, kinematic	: no data available	
Heat of combustion	: 34.77 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	able	
Chemical stability	able under normal conditi	ons.
Possibility of hazardous reactions	apours may form explosive o decomposition if stored	
Conditions to avoid	eat, flames and sparks. <tremes ar<="" of="" td="" temperature=""><td>nd direct sunlight.</td></tremes>	nd direct sunlight.
Incompatible materials	nines ases xidizing agents	
Hazardous decomposition products	arbon dioxide (CO2) arbon monoxide	

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:	
acetone: Acute oral toxicity	: LD50 rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 rat: 132 mg/l Exposure time: 3 h
	LC50 rat: 50.1 mg/l
Acute dermal toxicity	: LD50 guinea pig: > 7,426 mg/kg
	LD50 rabbit: > 7,426 mg/kg
propane: Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l Exposure time: 2 h
	LC50 rat: 658 mg/l Exposure time: 4 h
	LC50 rat: 1,355 mg/l
butane: Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l Exposure time: 2 h
	LC50 rat: 1,355 mg/l
Skin corrosion/irritation	
Product: Remarks: May cause skin irrita	ation in susceptible persons.
Serious eye damage/eye irritation <u>Product:</u>	1

Remarks: Eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Version 1.0

Revision Date 04/24/2015

Print Date 05/29/2015

Reproductive toxicity

no data available

acetone: propane: butane: Trade Secret:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: no data available
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
no data available	
Other adverse effects	
no data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S.

Version 1.0	Revision Date 04/24/2015	Print Date 05/29/2015
	Clean Air Act Section 602 (40 + B).	CFR 82, Subpt. A, App.A
Additional ecological information	: no data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*


*: Calculated RQ exceeds reasonably attainable upper limit.

HILLTARD QUICK &	& CLEAN VANILLA AIR FRES	HENER HILU104554
Version 1.0	Revision Date 04/24/2015	Print Date 05/29/2015
SARA 304 Extremely H	lazardous Substances Reportable Quanti	ity
This material does not c	ontain any components with a section 304 E	HS RQ.
SARA 311/312 Hazard	Is : Sudden Release of Pressure Haza Acute Health Hazard Fire Hazard	ard
SARA 302	: SARA 302: No chemicals in this m reporting requirements of SARA T	
SARA 313	: SARA 313: This material does not components with known CAS num threshold (De Minimis) reporting le Title III, Section 313.	bers that exceed the
California Prop 65	This product does not contain any California to cause cancer, birth de reproductive harm.	
The components of th	is product are reported in the following in	ventories:
TSCA DSL AICS NZIOC PICCS IECSC	On TSCA Inventory This product contains one or several comp Canadian DSL nor NDSL. Not in compliance with the inventory Not in compliance with the inventory Not in compliance with the inventory Not in compliance with the inventory	onents that are not on the
• · •		

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION



OSHA GHS Label Information:

Revision Date 04/24/2015

Print Date 05/29/2015

Hazard pictograms	
Signal word	: Danger:
Hazard statements	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:
	 Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Response: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

1000855

Version 1.0