



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** 868  
**Product name** Chalkboard Cleaner  
**Effective date** 01-Dec-2008  
**Company information** Claire Manufacturing  
500 Vista Ave.  
Addison, IL 60101 United States  
**Company phone** General Assistance 630-543-7600  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Version #** 12  
**Supersedes date** 18-Jul-2008

## 2. Hazards Identification

**Emergency overview** CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when exposed to heat or flame. May be ignited by heat, sparks or flames. Prolonged exposure may cause chronic effects.

**Potential health effects**

**Eyes** Health injuries are not known or expected under normal use.

**Skin** This product may be harmful if it is absorbed through the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Target organs** Kidney.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.  
Blood. Central nervous system. Liver. Respiratory system.

**Chronic effects** Unconsciousness. Liver injury may occur. Kidney injury may occur.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
2-Butoxyethanol	111-76-2	3 - 5
Ethyl Alcohol	64-17-5	3 - 5
Propane	74-98-6	1 - 3
n-Butane	106-97-8	1 - 3
Non-hazardous and other components below reportable levels		80 - 90

## 4. First Aid Measures

**First aid procedures**

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.

**Skin contact** Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

**Inhalation** Call a physician if symptoms develop or persist.

**Ingestion** Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

## 5. Fire Fighting Measures

### Extinguishing media

**Suitable extinguishing media** Large Fires: Water spray, fog or regular foam.

Small Fires: Dry chemical, CO<sub>2</sub>, water spray or regular foam.

### Protection of firefighters

#### Protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. Do not scatter spilled material with high pressure water streams.

## 6. Accidental Release Measures

### Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

### Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

## 7. Handling and Storage

### Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

### Storage

Level 1 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. Avoid exposure to long periods of sunlight. Keep out of the reach of children.

## 8. Exposure Controls / Personal Protection

### Exposure limits

#### ACGIH

##### Components

##### CAS #

##### TWA

##### STEL

##### Ceiling

2-Butoxyethanol

111-76-2

20 ppm

Not established

Not established

Ethyl Alcohol

64-17-5

1000 ppm

Not established

Not established

Propane

74-98-6

1000 ppm

Not established

Not established

n-Butane

106-97-8

1000 ppm

Not established

Not established

#### OSHA

##### Components

##### CAS #

##### TWA

##### STEL

##### Ceiling

2-Butoxyethanol

111-76-2

50 ppm

Not established

Not established

Ethyl Alcohol

64-17-5

1000 ppm

Not established

Not established

Propane

74-98-6

1000 ppm

Not established

Not established

### Personal protective equipment

#### Eye / face protection

Not normally needed.

#### Skin protection

Protective gloves.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

## 9. Physical & Chemical Properties

### Appearance

Compressed liquefied gas.

### Boiling point

206.6 °F (97.2 °C) estimated

### Color

Colorless.

### Flammability (HOC)

3.83 kJ/g

### Flash back

No

### Flash point

None

### Form

Aerosol.

Odor	Butyl
pH	9.5 - 10.5
Physical state	Liquid.
Pressure	70 - 90 psig @ 70F
Solubility	Completely
Specific gravity	0.9888 estimated

### 10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hazardous decomposition products	May include oxides of nitrogen.

### 11. Toxicological Information

Acute effects	Acute LD50: 5699 mg/kg estimated, Rat, Dermal Acute LC50: 56 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria. Possible reproductive hazard.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

### 12. Ecological Information

Ecotoxicity	LC50 28957 mg/L estimated, Fish, 96.00 Hours, EC50 43419 mg/L estimated, Daphnia, 48.00 Hours, IC50 12207 mg/L estimated, Algae, 72.00 Hours, Components of this product have been identified as having potential environmental concerns.
-------------	--

### 13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

### 14. Transport Information

#### Department of Transportation (DOT) Requirements

##### Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

#### IMDG

##### Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



**IATA****Basic shipping requirements:**

**Proper shipping name** Aerosols, flammable  
**Hazard class** 2.1  
**UN number** 1950  
**Additional information:**  
**Packaging exceptions** LTD QTY  
**Labels required** 2.1



<b>15. Regulatory Information</b>
-----------------------------------

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

2-Butoxyethanol	111-76-2	1.0 % de minimis concentration (applies to R-(OCH <sub>2</sub> CH <sub>2</sub> ) <sub>n</sub> -OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)
-----------------	----------	--

**Occupational Safety and Health Administration (OSHA)**

**29 CFR 1910.1200 hazardous chemical** Yes

**CERCLA (Superfund) reportable quantity**

None

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**  
 Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - No  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**Section 302 extremely hazardous substance** No

**Section 311 hazardous chemical** Yes

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations****U.S. - Pennsylvania - RTK (Right to Know) List**

2-Butoxyethanol	111-76-2	Present
Ethyl Alcohol	64-17-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present

<b>16. Other Information</b>
------------------------------

**HMIS® ratings**

Health: 1  
 Flammability: 1  
 Physical hazard: 0

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**MSDS sections updated**

Product and Company Identification: Alternate Trade Names  
Physical & Chemical Properties: Physical & Chemical Properties