

T. BAKER CHEMICAL CO. 222 RED SCHOOL LANE, PHILLIPSBURG, NJ 08865

M A T E R I A L S A F E T Y D A T A S H E E T

24-HOUR EMERGENCY TELEPHONE --- (201) 859-2151

CHEMTREC # (800) 424-9300 -- NATIONAL RESPONSE CENTER # (800) 424-8802

8 -01

CALCIUM HYPOCHLORITE

PAGE: 1

EFFECTIVE: 09/27/85

ISSUED: 01/23/86

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: CALCIUM HYPOCHLORITE
 FORMULA: CaCl₂O₂
 FORMULA WT: 142.99
 U.S. NO.: 07778-54-3
 OSHA/RTECS NO.: NH3485000
 COMMON SYNONYMS: HYPOCHLOROUS ACID; CALCIUM SALT; LOSANTIN; CALCIUM HYPOCHLORIDE
 PRODUCT CODES: 1378

PRECAUTIONARY LABELLING

BAKER SAF-T-DATA(TM) SYSTEM

HEALTH	-	2	
FLAMMABILITY	-	0	
REACTIVITY	-	3	(OXIDIZER)
CONTACT	-	2	

LABORATORY PROTECTIVE EQUIPMENT

SAFETY GLASSES; LAB COAT; VENT HOOD; PROPER GLOVES

PRECAUTIONARY LABEL STATEMENTS

DANGER
 STRONG OXIDIZER - CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE
 HARMFUL IF SWALLOWED
 CAUSES IRRITATION

KEEP FROM CONTACT WITH CLOTHING AND OTHER COMBUSTIBLE MATERIALS. DO NOT STORE NEAR COMBUSTIBLE MATERIALS. AVOID CONTACT WITH EYES, SKIN, CLOTHING. KEEP IN TIGHTLY CLOSED CONTAINER. WASH THOROUGHLY AFTER HANDLING. IN CASE OF FIRE, SOAK WITH WATER. IN CASE OF SPILL, SWEEP UP AND REMOVE. FLUSH SPILL AREA WITH WATER.

SECTION II - HAZARDOUS COMPONENTS

COMPONENT	%	CAS NO.
CALCIUM HYPOCHLORITE	90-100	7778-54-3

SECTION III - PHYSICAL DATA

BOILING POINT:	N/A	VAPOR PRESSURE(MM HG):	N/A
MELTING POINT:	N/A	VAPOR DENSITY(AIR=1):	6.9
SPECIFIC GRAVITY: (H ₂ O=1)	2.35	EVAPORATION RATE: (BUTYL ACETATE=1)	N/A

C-18 -01
EFFECTIVE: 09/27/85

CALCIUM HYPOCHLORITE

ISSUED: 01/2

SECTION III - PHYSICAL DATA (CONTINUED)

SOLUBILITY(H₂O): APPRECIABLE (MORE THAN 10 %) % VOLATILES BY VOLUME: 0
APPEARANCE & ODOR: WHITE POWDER WITH STRONG CHLORINE-LIKE ODOR.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A
NFPA 704M RATING: 1-0-2
FIRE EXTINGUISHING MEDIA
USE WATER SPRAY.

SPECIAL FIRE-FIGHTING PROCEDURES

FIREFIGHTERS SHOULD WEAR PROPER PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE. MOVE CONTAINERS FROM FIRE AREA IF IT CAN BE DONE WITHOUT RISK. USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

UNUSUAL FIRE & EXPLOSION HAZARDS

STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE.
CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE.

TOXIC GASES PRODUCED
HYDROGEN CHLORIDE

SECTION V - HEALTH HAZARD DATA

TOXICITY: LD50 (ORAL-RAT) (MG/KG) - 850

EFFECTS OF OVEREXPOSURE

CONTACT WITH SKIN MAY CAUSE ULCERS, LOCAL DISCOLORATION, ECZEMA.
CONTACT WITH SKIN OR EYES MAY CAUSE SEVERE IRRITATION OR BURNS.
EXCESSIVE INHALATION OF DUST IS IRRITATING AND MAY BE SEVERELY DAMAGING TO RESPIRATORY PASSAGES AND/OR LUNGS.
INGESTION MAY CAUSE SEVERE BURNING TO MOUTH AND STOMACH.
INGESTION MAY BE FATAL.

EMERGENCY AND FIRST AID PROCEDURES

CALL A PHYSICIAN.
IF SWALLOWED, IF CONSCIOUS, IMMEDIATELY INDUCE VOMITING.
IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES OR SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES.
WASH CLOTHING BEFORE RE-USE.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

8 -01
EFFECTIVE: 09/27/85

CALCIUM HYPOCHLORITE

PAGE: 3
ISSUED: 01/23/86

SECTION VI - REACTIVITY DATA (CONTINUED)

CONDITIONS TO AVOID: MOISTURE, HEAT, SHOCK

INCOMPATIBLES: WATER, COMBUSTIBLE MATERIALS, STRONG REDUCING AGENTS

DECOMPOSITION PRODUCTS: HYDROGEN CHLORIDE

SECTION VII - SPILL AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN THE EVENT OF A SPILL OR DISCHARGE

WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.
KEEP COMBUSTIBLES (WOOD, PAPER, OIL, ETC.) AWAY FROM SPILLED MATERIAL.
WITH CLEAN SHOVEL, CAREFULLY PLACE MATERIAL INTO CLEAN, DRY CONTAINER AND
COVER; REMOVE FROM AREA. FLUSH SPILL AREA WITH WATER.

DISPOSAL PROCEDURE

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL
ENVIRONMENTAL REGULATIONS.

EPA HAZARDOUS WASTE NUMBER: D003 (REACTIVE WASTE)

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: USE ADEQUATE GENERAL OR LOCAL EXHAUST VENTILATION
TO KEEP FUME OR DUST LEVELS AS LOW AS POSSIBLE.

RESPIRATORY PROTECTION: NONE REQUIRED WHERE ADEQUATE VENTILATION
CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS
HIGH, USE AN APPROPRIATE RESPIRATOR OR DUST MASK.

EYE/SKIN PROTECTION: SAFETY GLASSES WITH SIDESHIELDS, UNIFORM, NEOPRENE
GLOVES ARE RECOMMENDED.

SECTION IX - STORAGE AND HANDLING PRECAUTIONS

SAF-T-DATA(TM) STORAGE COLOR CODE: YELLOW

SPECIAL PRECAUTIONS

KEEP CONTAINER TIGHTLY CLOSED. STORE SEPARATELY AND AWAY FROM FLAMMABLE
AND COMBUSTIBLE MATERIALS.

SECTION X - TRANSPORTATION DATA AND ADDITIONAL INFORMATION

DOMESTIC (D.O.T.)

PROPER SHIPPING NAME	BLEACHING POWDER (CONTAINING (39% CL)(WATER ONLY)
HAZARD CLASS	ORM-C
UN	UN2208
LABELS	NONE

CONTINUED ON PAGE: 4

