### Safety Data Sheet

Printing date 03/02/2015 Revised On 03/02/2015

### 1 Identification of the substance and manufacturer

Trade name:

Product code: 4102

Paints and coatings. Product category Manufacturer/Supplier: Atco International 1401 Barclay Circle, S.E. Marietta, GA 30060 Phone: 770-424-7550

**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

H351 Suspected of causing cancer. Carc. 2

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Skin Irrit. 2 H315 Causes skin irritation.

**GHS Hazard pictograms** 

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Causes skin irritation.
Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. If medical advice is needed, have product container or label at hand. **Precautionary statements** 

Keep out of reach of children.

Read label before use

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray. If skin irritation occurs: Get medical advice/attention. If on skin: Wash with plenty of water. Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

| This product is a mixture of the substances helds below with horning arded additions. |        |
|---|--------|
|   |        |
|   | 18.95% |
|   | 13.89% |
|   | 11.13% |
|   | 9.76%  |
|   | 6.07%  |
|   | 5.4%   |
|   | 2.39%  |
|   | 2.31%  |
|   | 1.47%  |
|   |        |

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact:

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects: Indication of any immediate medical

attention needed:

No further relevant information available.

Printing date 03/02/2015 Revised On 03/02/2015

Trade name: NEW WHITE

(Contd. of page 1)

5 Fire-fighting measures

**Extinguishing agents:** Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for

containment and cleaning up: Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing Storage requirements:

conditions. Store locked up.

#### 8 Exposure controls/personal protection

refer to Appendix F

| Cor | Components with limit values that require monitoring at the workplace: |                                       |  |  |  |
|-----|--|---------------------------------------|--|--|--|
| 74- | 74-98-6 propane  |                                       |  |  |  |
| PEl | L (USA)  | Long-term value: 1800 mg/m³, 1000 ppm |  |  |  |
| REI | L (USA)  | Long-term value: 1800 mg/m³, 1000 ppm |  |  |  |

108-88-3 Toluene

TLV (USA)

PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

Short-term value: 560 mg/m³, 150 ppm REL (USA)

Long-term value: 375 mg/m³, 100 ppm Long-term value: 75 mg/m³, 20 ppm TLV (USA)

BEI

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm Short-term value: 2370 mg/m³, 1000 ppm TLV (USA)

1330-20-7 xylene (mix)

PEL (USA) REL (USA) Long-term value: 435 mg/m³, 100 ppm Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (USA) BE

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

### Ingredients with biological limit values:

## 108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

0.03 mg/L

Time: prior to last shift of workweek Parameter: Toluene

Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

## 1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine Medium: urine

Time: end of shift Parameter: Methylhippuric acids

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be **Breathing equipment:** worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

(Contd. on page 3)

Safety Data Sheet

Printing date 03/02/2015 Revised On 03/02/2015

**Trade name: NEW WHITE** 

Eye protection: Tightly sealed goggles (Contd. of page 2)

### 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F) Flash point: -19 °C (-2 °F) Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined.

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined Viscosity: Not determined. **VOC** content: 571.9 g/l / 4.77 lb/gl

56.8 % **VOC** content (less exempt solvents): Water: 21.3 % MIR Value: 1.10 Solids content: 21.7 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing Conditions to avoid:

temperatures. Not fully evaluated.

Chemical stability: No dangerous reactions known. Possibility of hazardous reactions:

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

### 11 Toxicological information

| LD/LC50    | LD/LC50 values that are relevant for classification:     |                       |  |  |  |
|------------|--|-----------------------|--|--|--|
| 106-97-8 ו | 106-97-8 n-butane  |                       |  |  |  |
| Inhalative | Inhalative LC50/4 h 658 mg/l (rat)                       |                       |  |  |  |
| 13463-67-  | 13463-67-7 titanium dioxide                              |                       |  |  |  |
| Oral       |  | >20000 mg/kg (rat)    |  |  |  |
| Dermal     | LD50   | >10000 mg/kg (rbt)    |  |  |  |
| Inhalative | LC50/4 h   | >6.82 mg/l (rat)      |  |  |  |
| 1330-20-7  | 1330-20-7 xylene (mix)                                   |                       |  |  |  |
| Oral       | LD50   | 8700 mg/kg (rat)      |  |  |  |
| Dermal     | LD50   | 2000 mg/kg (rbt)      |  |  |  |
| Inhalative | LC50/4 h   | 6350 mg/l (rat)       |  |  |  |
| 108-65-6   | 108-65-6 PM acetate                                      |                       |  |  |  |
| Oral       | LD50   | 8500 mg/kg (rat)      |  |  |  |
|            |  | 35.7 mg/l (rat)       |  |  |  |
|            | Information on toxicological effects: No data available. |                       |  |  |  |
| Skin effec |  | No irritant effect.   |  |  |  |
| Eye effect | S.   | No irritating effect. |  |  |  |

Sensitization: No sensitizing effects known.

Carcinogenic categories

| IARC (International Agency for Research on Cancer) |    |
|--|----|
| 108-88-3 Toluene                                   | 3  |
| 13463-67-7 titanium dioxide                        | 2B |
| 1330-20-7 xylene (mix)                             | 3  |
| NTP (National Toxicology Program)                  |    |
| None of the ingredients is listed.                 |    |

### 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

(Contd. on page 4)

Ш

(Contd. of page 3)

# Safety Data Sheet

Printing date 03/02/2015 Revised On 03/02/2015

**Trade name: NEW WHITE** 

No further relevant information available.

Bioaccumulative potential: Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

14 Transport information

**UN-Number** UN1950

DOT N/A

DOT **Consumer Commodity** Aerosols, flammable **ADR** 1950 Aerosols

Transport hazard class(es):

2.1 **Class** Marine pollutant: No

Warning: Gases F-D,S-U Special precautions for user:

**EMS Number:** 

**Quantity limitations** On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

**ADR** 

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

**IMDG** 

Limited quantities (LQ)

Code: E0 **Excepted quantities (EQ)** 

Not permitted as Excepted Quantity **Packaging Group:** 

**UN "Model Regulation":** UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

1330-20-7 xylene (mix)

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. CPSC:

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene
California Proposition 65 chemicals

known to cause developmental toxicity

CANADIAN ENVIRONMENTAL

108-88-3 Toluene

**PROTECTION ACT:** All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

108-88-3 Toluene 1330-20-7 xylene (mix)

16 Other information Contact: Regulatory Affairs 03/02/2015 / -Date of preparation / last revision