



# MSDS Material Safety Data Sheet

PROFILE Products, LLC

TURFACE®

MSDS Number: BLM001

Revision Date: 2/22/08

Page 1 of 4

## 1 PRODUCT AND COMPANY IDENTIFICATION

### Manufacturer

PROFILE Products, LLC  
750 LAKE COOK ROAD  
SUITE 440  
BUFFALO GROVE, IL 60089

Contact:  
Telephone Number:(847) 215-1144  
FAX Number: (847) 215-0577  
E-Mail: profileproducts.com  
Web www.profileproducts.com

Product Name: TURFACE®  
Revision Date: 2/22/08  
MSDS Number: BLM001  
Common Name: N/A  
CAS Number: 70892-59-0

Description: Heat Treated Montmorillonite Clay Mineral.

## 2 HAZARDS IDENTIFICATION

### Route of Entry:

Inhalation: Lungs

### Skin Contact:

No

### Eye Contact:

No

### Ingestion:

NFPA-ratings (scale 0-4): Health = 0, Fire = 0, Reactivity = 0

Crystalline Silica (Quartz) [EPA Hazard Category: Health]

Carcinogen: OSHA - No NTP - Yes (respirable) IARC - Yes


This product contains up to 5% crystalline silica. The International Agency for Research on Cancer (IARC) has stated that there is sufficient evidence of carcinogenicity of crystalline silica to human beings. It was noted that carcinogenicity was not detected in all industrial circumstances studied. The NTP's Sixth Annual Report on Carcinogens include respirable crystalline silica. The Hazard Communication Standard (29CFR 1910.1200) requires that any material containing over 0.1% of a substance reported as a carcinogen in an IARC monograph or the most recent NTP Annual Report on Carcinogens must be identified as a carcinogen. These identifications are for hazard communications only and do not serve as assessments of carcinogenic risk. Crystalline silica is known to cause silicosis. At dust levels below the recommended PEL exposure to the crystalline silica contained in this product should not present a health hazard.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

### Ingredients:

Cas # Perc. Chemical Name

# MSDS Material Safety Data Sheet



TURFACE®

MSDS Number: BLM001

Revision Date: 2/22/08

14808607 3 - 5 % | silica, crystalline quartz

Page 2 of 4

4

## FIRST AID MEASURES

**Inhalation:**  
**Skin Contact:** Wash thoroughly with soap and water.  
**Eye Contact:** Flush thoroughly with water. See a physician if discomfort persists.  
**Ingestion:**

5

## FIRE FIGHTING MEASURES

Non-flammable and non-hazardous

6

## ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.

7

## HANDLING AND STORAGE


**Handling Precautions:** Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.  
**Storage Requirements:** Do not store near vegetable oil or turpentine.

8

## EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use NIOSH-approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are completed.  
 Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than Permissible Exposure Limits is recommended.  
 Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust exposure to the eyes.  
 Other Protective Equipment: Optional.

# MSDS Material Safety Data Sheet



TURFACE®

MSDS Number: BLM001

Revision Date: 2/22/08

Page 3 of 4

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Brown to buff-colored granular particles  
 Physical State: Negligible  
 Odor: Negligible  
 pH: N.A.  
 Vapor Pressure: N.A.  
 Vapor Density: Negligible  
 Bulk Density: 35 lbs/cubic ft.

## 10 STABILITY AND REACTIVITY

Stability: Turface is stable under all normal conditions.  
 Conditions to avoid: Unreacted polymer monomers  
 Materials to avoid (incompatibility):  
 Hazardous Decomposition products: Will not occur. However, contact with vegetable oil or turpentine may cause evolution of heat.  
 Hazardous Polymerization:

## 11 TOXICOLOGICAL INFORMATION

Inhalation - N.E.  
 Intravenous - Rat - LD50: 15mg/kg  
 Oral - Rat - LD50: 3160 mg/kg

## 12 ECOLOGICAL INFORMATION

## 13 DISPOSAL CONSIDERATIONS


Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

## 14 TRANSPORT INFORMATION

DOT Class: Not regulated #

# **MSDS** Material Safety Data Sheet

PROFILE Products, LLC



TURFACE®

MSDS Number: BLM001

Revision Date: 2/22/08

Page 4 of 4

15

## REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

\*Silica, crystalline quartz (14808607 n/a%) MASS, NRC, OSHAWAC, PA, TXAIR

## REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List  
NRC = Nationally Recognized Carcinogens  
OSHA = OSHA Workplace Air Contaminants  
OSHAWAC = OSHA Workpiece Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level

16

## OTHER INFORMATION

END OF MSDS DOCUMENT