

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by U.S. Department of Labor - Essential Similar - to Form OSHA-20)

SEPTEMBER 2009

Page 1

SECTION I

Manufactured for: **Worldwide Vinyl Repair Systems**
P.O. Box 939
Rt. 1, Box 619064
Kirbyville, Texas 75956
409-423-4696
800-642-5456

Product Class: **Poly (Vinyl Chloride) Plastisol T-004**

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>Percent</u>	<u>mg/Cubic Meter</u>
Barium as Metallic Salt	Less than 1%	0.5

SECTION III - PHYSICAL DATA

Boiling Range- Solidifies Vapor Density- Lighter than Air
 Evaporation Rate- Slower than Ether
 % Volatile by volume 0
 Weight per Gallon 8.3 lbs

SECTION IV - FIRE AND EXPLOSION HAZARD

DOT Category: Not applicable Flashpoint: LEL
 Extinguishing Media: Water spray, foam, dry chemical, CO2 or material for class B fires
 Unusual fire and Explosion Hazards: None
 Special Fire Fighting Procedures - May produce toxic fumes. Use self-contained breathing apparatus

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value Effects of Overexposure - Handle in accordance with good industrial hygiene and safety practices. Avoid unnecessary exposure and remove from skin, clothing and eyes.
 Emergency and First Aid Procedures - Does not present significant eye irritation or eye toxicity requiring special protection.

