



SUBFLOOR ADHESIVE

MATERIAL SAFETY DATA SHEET

GRSUBA28VS-VOC-Compliant Solvent

1. Product and company identification

Company and address	PrimeSource Building Products, Inc. 1321 Greenway Drive Irving, TX 75038-2504
Contact	PrimeSource Building Products, Inc.
Telephone	(800) 676-7777
In case of emergency	
Chemtrec (24 Hour)	(800) 424-9300
Chemtrec International	(703) 527-3887
Product code	750202
Date of revision	5/10/2013
Print date	5/10/2013
Product use	Construction adhesive Proprietary polymer

2. Hazards identification

Emergency overview

Physical state	Liquid [Paste]
Color	Beige
Odor	Solvent(s) [Strong]
Signal word	DANGER!
Hazard statements	EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER.
Precautionary measures	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Routes of entry

Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation	Toxic by inhalation. Irritating to respiratory system. Inhalation causes headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.
Ingestion	Harmful if swallowed.
Skin	Irritating to skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Eyes	Moderately irritating to eyes. This product may irritate eyes upon contact.

2. Hazards identification-continued

Potential chronic health effects

Chronic effects	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity	Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Target organs	Contains material which may cause damage to the following organs: the nervous system, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Over-exposure signs/symptoms

Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	No specific data.
Skin	Adverse symptoms may include the following: irritation redness dryness cracking
Eyes	Adverse symptoms may include the following: irritation watering redness
Medical conditions aggravated by overexposure	None known.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
methyl acetate	79-20-9	25 - 50
n-hexane	110-54-3	1 - 5
vinyl acetate	108-05-4	0.1 - 0.5

Canada

Name	CAS number	%
methyl acetate	79-20-9	25 - 50
n-hexane	110-54-3	1 - 5
methanol	67-56-1	0.1 - 0.5
vinyl acetate	108-05-4	0.1 - 0.5

Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
methyl acetate	79-20-9	UN1993	25 - 50	3100 ppm	2	3	0	-
n-hexane	110-54-3	UN1993	1 - 5	1100 ppm	1	3	0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product	Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Extinguishing media	
Suitable	Use dry chemical, CO ₂ , water spray (fog) or foam.
Not suitable	Do not use water jet.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Absorb with an inert material.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store between the following temperatures: -17 to 40°C (1.4 to 104°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
methyl acetate	<p>ACGIH TLV (United States, 3/2012). TWA: 200 ppm 8 hour(s). TWA: 606 mg/m³ 8 hour(s). STEL: 250 ppm 15 minute(s). STEL: 757 mg/m³ 15 minute(s).</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 200 ppm 8 hour(s). TWA: 610 mg/m³ 8 hour(s). STEL: 250 ppm 15 minute(s). STEL: 760 mg/m³ 15 minute(s).</p> <p>NIOSH REL (United States, 6/2009). TWA: 200 ppm 10 hour(s). TWA: 610 mg/m³ 10 hour(s). STEL: 250 ppm 15 minute(s). STEL: 760 mg/m³ 15 minute(s).</p> <p>OSHA PEL (United States, 6/2010). TWA: 200 ppm 8 hour(s). TWA: 610 mg/m³ 8 hour(s).</p>
n-hexane	<p>OSHA PEL 1989 (United States, 3/1989). TWA: 50 ppm 8 hour(s). TWA: 180 mg/m³ 8 hour(s).</p> <p>NIOSH REL (United States, 6/2009). TWA: 50 ppm 10 hour(s). TWA: 180 mg/m³ 10 hour(s).</p> <p>ACGIH TLV (United States, 3/2012). Absorbed through skin. TWA: 50 ppm 8 hour(s).</p> <p>OSHA PEL (United States, 6/2010). TWA: 500 ppm 8 hour(s). TWA: 1800 mg/m³ 8 hour(s).</p>

Ingredients continued on next page

8. Exposure controls/personal protection-continued

Ingredient	Exposure limits
vinyl acetate	<p>ACGIH TLV (United States, 3/2012). TWA: 10 ppm 8 hour(s). TWA: 35 mg/m³ 8 hour(s). STEL: 15 ppm 15 minute(s). STEL: 53 mg/m³ 15 minute(s).</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 10 ppm 8 hour(s). TWA: 30 mg/m³ 8 hour(s). STEL: 20 ppm 15 minute(s). STEL: 60 mg/m³ 15 minute(s).</p> <p>NIOSH REL (United States, 6/2009). CEIL: 4 ppm 15 minute(s). CEIL: 15 mg/m³ 15 minute(s).</p>

Canada

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			Notations
Ingredient	List name	ppm	mg/m ³	Other	ppm	mg/m ³	Other	ppm	mg/m ³	Other	
methyl acetate	US ACGIH 3/2012	200	606	-	250	757	-	-	-	-	
	AB 4/2009	200	606	-	250	757	-	-	-	-	
	BC 4/2012	200	-	-	250	-	-	-	-	-	
	ON 7/2010	200	606	-	250	757	-	-	-	-	
	QC 9/2011	200	606	-	250	757	-	-	-	-	
n-hexane	US ACGIH 3/2012	50	-	-	-	-	-	-	-	-	[1]
	AB 4/2009	50	176	-	-	-	-	-	-	-	[1]
	BC 4/2012	20	-	-	-	-	-	-	-	-	[1]
	ON 7/2010	50	-	-	-	-	-	-	-	-	[1]
	QC 9/2011	50	176	-	-	-	-	-	-	-	[1]
methanol	US ACGIH 3/2012	200	262	-	250	328	-	-	-	-	[1]
	AB 4/2009	200	262	-	250	328	-	-	-	-	[1]
	BC 4/2012	200	-	-	250	-	-	-	-	-	[1]
	ON 7/2010	200	262	-	250	328	-	-	-	-	[1]
	QC 9/2011	200	262	-	250	328	-	-	-	-	[1]
vinyl acetate	US ACGIH 3/2012	10	35	-	15	53	-	-	-	-	
	AB 4/2009	10	35	-	15	53	-	-	-	-	
	BC 4/2012	10	-	-	15	-	-	-	-	-	
	ON 7/2010	10	35	-	15	53	-	-	-	-	
	QC 9/2011	10	35	-	15	53	-	-	-	-	

[1] Absorbed through skin.

Mexico

Occupational exposure limits

Ingredient	Exposure limits
methyl acetate	<p>NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 200 ppm 8 hour(s). LMPE-PPT: 610 mg/m³ 8 hour(s). LMPE-CT: 760 mg/m³ 15 minute(s). LMPE-CT: 250 ppm 15 minute(s).</p>
n-hexane	<p>NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 50 ppm 8 hour(s). LMPE-PPT: 176 mg/m³ 8 hour(s).</p>

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8. Exposure controls/personal protection-continued

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Respiratory	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eyes	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

Physical state	Liquid [Paste]
Flash point	Closed cup: -18°C (-0.4°F) [Setaflash]
Auto-ignition temperature	252°C (485.6°F)
Color	Beige
Odor	Solvent(s) [Strong]
Boiling/condensation point	54.444°C (130°F)
Relative density	1.2638
Volatility	34.72% (w/w)
Evaporation rate	>1 (butyl acetate = 1)
VOC (less water, less exempt solvents)	49 g/L
Solubility	Insoluble in the following materials: cold water and hot water.

10. Stability and reactivity

Chemical stability	The product is stable.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	Highly reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.
Incompatibility	Reactive or incompatible with the following materials: metals, acids and alkalis.
Conditions of reactivity	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

11. Toxicological information

United States

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
n-hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-
vinyl acetate	LC50 Inhalation Vapor	Rat	11400 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2335 mg/kg	-
	LD50 Oral	Rat	2900 mg/kg	-

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
methyl acetate	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
n-hexane	Eyes - Mild irritant	Rabbit	-	10 milligrams	-

Conclusion/Summary

Skin

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes

This product may irritate eyes upon contact.

Respiratory

High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.

Sensitizer

No known significant effects or critical hazards.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
vinyl acetate	A3	2B	-	-	-	-

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Canada

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
n-hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-
methanol	LC50 Inhalation Gas.	Rat	145000 ppm	1 hours
	LC50 Inhalation Gas.	Rat	64000 ppm	4 hours
vinyl acetate	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
	LC50 Inhalation Vapor	Rat	11400 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2335 mg/kg	-
	LD50 Oral	Rat	2900 mg/kg	-

11. Toxicological information-continued

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
methyl acetate	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
n-hexane methanol	Eyes - Mild irritant	Rabbit	-	10 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	40 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-

Conclusion/Summary

Skin

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes

This product may irritate eyes upon contact.

Respiratory

High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.

Sensitizer

No known significant effects or critical hazards.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
vinyl acetate	A3	2B	-	-	-	-

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Mexico

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
n-hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
-	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
-	Eyes - Mild irritant	Rabbit	-	10 milligrams	-

11. Toxicological information-continued

Conclusion/Summary

Skin	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Eyes	This product may irritate eyes upon contact.
Respiratory	High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.

Sensitizer

No known significant effects or critical hazards.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
vinyl acetate	A3	2B	-	-	-	-

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
methyl acetate	Acute LC50 320000 to 348000 ug/L Fresh water	Fish - Pimephales promelas - 28 to 32 days - 17.5 mm - 0.087 g	96 hours
n-hexane	Acute LC50 2500 to 2980 ug/L Fresh water	Fish - Pimephales promelas - 31 days - 20.4 mm - 0.123 g	96 hours
vinyl acetate	Acute LC50 10000 to 100000 ug/L Marine water	Crustaceans - Crangon crangon - Larvae	48 hours
	Acute LC50 14000 ug/L Fresh water	Fish - Pimephales promelas - 1 days	96 hours

Persistence/degradability

No known significant effects or critical hazards.

Canada

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
methyl acetate	Acute LC50 320000 to 348000 ug/L Fresh water	Fish - Pimephales promelas - 28 to 32 days - 17.5 mm - 0.087 g	96 hours
n-hexane	Acute LC50 2500 to 2980 ug/L Fresh water	Fish - Pimephales promelas - 31 days - 20.4 mm - 0.123 g	96 hours
methanol	Acute EC50 16.912 mg/L Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 ug/L Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 to 4395 mg/L Fresh water	Daphnia - Daphnia magna - Neonate - <24 hours	48 hours
	Acute LC50 100000 ug/L Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) - 0.2 to 0.5 g	96 hours
vinyl acetate	Acute LC50 10000 to 100000 ug/L Marine water	Crustaceans - Crangon crangon - Larvae	48 hours
	Acute LC50 14000 ug/L Fresh water	Fish - Pimephales promelas - 1 days	96 hours

Persistence/degradability

No known significant effects or critical hazards.

12. Ecological information-continued

Mexico

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
methyl acetate	Acute LC50 320000 to 348000 ug/L Fresh water	Fish - Pimephales promelas - 28 to 32 days - 17.5 mm - 0.087 g	96 hours
n-hexane	Acute LC50 2500 to 2980 ug/L Fresh water	Fish - Pimephales promelas - 31 days - 20.4 mm - 0.123 g	96 hours

Persistence/degradability No known significant effects or critical hazards.

13. Disposal considerations







Waste disposal

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	1133	ADHESIVES, containing flammable liquid	3	III		Remarks Limited quantity
TDG Classification	1133	ADHESIVES, containing flammable liquid	3	III		Remarks Limited quantity
Mexico Classification	1133	ADHESIVES, containing flammable liquid	3	III		Remarks Limited quantity
ADR/RID Class	1133	ADHESIVES, containing flammable liquid	3	III		Remarks Limited quantity
IMDG Class						Remarks Limited quantity
IATA-DGR Class	1133	ADHESIVES, containing flammable liquid	3	III		-

PG* : Packing group

15. Regulatory information

United States

HCS Classification Flammable liquid
Toxic material
Irritating material
Carcinogen

U.S. Federal regulations

TSCA 8(a) PAIR: methyl acetate; mequinol

TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: methyl acetate; n-hexane

SARA 311/312 MSDS distribution - chemical inventory - hazard identification:

Grip-Rite® Subfloor Adhesive-VOC-Compliant Solvent: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) Listed

Clean Air Act Section 602 Class I Substances Not listed

Clean Air Act Section 602 Class II Substances Not listed

DEA List I Chemicals (Precursor Chemicals) Not listed

DEA List II Chemicals (Essential Chemicals) Not listed

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	n-hexane	110-54-3	1 - 5
	vinyl acetate	108-05-4	0.1 - 0.5
Supplier notification	n-hexane	110-54-3	1 - 5
	vinyl acetate	108-05-4	0.1 - 0.5

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

Massachusetts The following components are listed: METHYL ACETATE; HEXANE

New York The following components are listed: VINYL ACETATE; HEXANE

New Jersey The following components are listed: METHYL ACETATE; ACETIC ACID, METHYL ESTER; VINYL ACETATE; ACETIC ACID ETHENYL ESTER; n-HEXANE; HEXANE

Pennsylvania The following components are listed: ACETIC ACID, METHYL ESTER; ACETIC ACID ETHENYL ESTER; HEXANE

15. Regulatory information-continued

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
methanol	No.	Yes.	45000 µg/day (ingestion) 47000 µg/day (inhalation)	No.

Canada

WHMIS (Canada)

Class B-2: Flammable liquid
Class D-2A: Material causing other toxic effects (Very toxic).
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI

The following components are listed: n-Hexane

CEPA Toxic substances

None of the components are listed.

Canada inventory

All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification



International regulations

International lists

Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

Korea inventory: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Chemical Weapons

Not listed

Convention List Schedule I Chemicals

Chemical Weapons

Not listed

Convention List Schedule II Chemicals

Chemical Weapons

Not listed

Convention List Schedule III Chemicals

16. Other information

Label requirements

EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER.

Hazardous Material Information System (U.S.A.)

Health	2
Flammability	3
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing	5/10/2013
Date of issue	5/10/2013
Date of previous issue	1/9/2013
Version	2

■ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

PRIME SOURCE
BUILDING PRODUCTS, INC.

© 2013 PrimeSource Building Products, Inc.

800-676-7777
www.grip-rite.com
www.primesourcebp.com

Grip-Rite™ adhesives, sealants and caulks are distributed by PrimeSource Building Products, Inc.

Grip-Rite is a trademark of PrimeSource Building Products, Inc. Other product and company names listed may be trademarks of their respective owners.