

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 1

Printed: 04/20/2015

Revision: 04/20/2015

Supersedes Revision: 09/08/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Klean Strip Paint Thinner	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact:	3E 24 Hour Emergency Contact	(800)451-8346
Information:	W.M. Barr Customer Service	(800)398-3892
Intended Use:	Paint, stain, and varnish thinning.	
Synonyms:	CKPT94402, GKPT94002B, DKPT94403CA, EKPT94401, GKPT94002, GKPT94002P, GKPT94002T, GKPT94400, GPT1KS, PA12779, QKPT94003, QKPT94203, QPT1KS, GKPTDP	
Additional Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 3
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2B
Toxic To Reproduction, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 2
Aspiration Toxicity, Category 1



GHS Signal Word: Danger

GHS Hazard Phrases: H226: Flammable liquid and vapor.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H320: Causes eye irritation.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H361: Suspected of damaging fertility or the unborn child if inhaled.
H373: May cause damage to cardiovascular system and central nervous system through prolonged or repeated exposure.

GHS Precaution Phrases: P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe gas/mist/vapors/spray.
P264: Wash hands thoroughly after handling.

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 2

Printed: 04/20/2015

Revision: 04/20/2015

Supersedes Revision: 09/08/2014

GHS Response Phrases:


P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P281: Use personal protective equipment as required.
P235: Keep cool.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313: IF exposed or concerned: Get medical attention/advice.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P314: Get medical attention/advice if you feel unwell.
P321: Specific treatment see label.
P331: Do NOT induce vomiting.
P332+313: If skin irritation occurs, get medical advice/attention.
P337+313: If eye irritation persists, get medical advice/attention.
P362: Take off contaminated clothing and wash before re-use.
P370+378: In case of fire, use dry chemical powder to extinguish.

GHS Storage and Disposal Phrases:

P403+233: Store container tightly closed in well-ventilated place.
P405: Store locked up.
P501: Dispose of contents/container according to local, state and federal regulations.

Hazard Rating System:

HEALTH	*	1
FLAMMABILITY		2
PHYSICAL		0
PPE		

**HMIS:****OSHA Regulatory Status:**

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):**Inhalation Acute Exposure Effects:**

May cause dizziness; headache; watering of eyes; eye irritation; weakness; nausea; muscle twitches, and depression of central nervous system. Severe overexposure may cause convulsions; unconsciousness; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

Ingestion Acute Exposure Effects:

Harmful or fatal if swallowed. May cause nausea; weakness; muscle twitches; gastrointestinal irritation; and diarrhea. Severe overexposure may cause convulsions; unconsciousness; and death.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 3

Printed: 04/20/2015

Revision: 04/20/2015

Supersedes Revision: 09/08/2014

dermatitis. May cause jaundice; bone marrow damage; liver damage; anemia; and skin irritation.

Medical Conditions Generally Aggravated By Exposure: Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
64742-47-8	Hydrotreated light distillate (petroleum)	<=100.0 %	OA5504000
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<=100.0 %	NA
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	<=95.0 %	WJ8925000
25550-14-5	Benzene, Ethylmethyl-	<=1.5 %	NA
25551-13-7	Benzene, Trimethyl-	<=1.5 %	DC3220000
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	<=1.0 %	DC3325000
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	<=1.0 %	ZE2100000
103-65-1	Benzene, Propyl- {N-Propylbenzene}	<=1.0 %	DA8750000

Additional Chemical Information Ingredients vary due to multiple blends and/or raw material suppliers

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or artificial medical assistance can be rendered.

Skin Contact:

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

Ingestion:

Do not induce vomiting. Call your local poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.

If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to a person who is not fully conscious. Do not leave victim unattended. Seek medical attention immediately.

Signs and Symptoms Of Exposure:

Inhalation, ingestion, and dermal are possible routes of exposure.

Note to Physician:

Call your local poison control center for further information.

Inhalation: Inhalation overexposure can produce toxic effects. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation as required.

Ingestion: If ingested, this material presents a significant aspiration and chemical

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 4

Printed: 04/20/2015

Revision: 04/20/2015

Supersedes Revision: 09/08/2014

pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

5. FIRE FIGHTING MEASURES

Flash Pt:	NFPA Class II > 100.00 F
Explosive Limits:	LEL: 0.5 UEL: 6
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Use carbon dioxide, dry chemical powder, or foam.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	Combustible Liquid.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. Large spills: Dike far ahead of spill for later disposal. Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container. A static electrical charge can accumulate when this material is flowing through pipes, nozzles or filters, and when it is agitated. A static spark discharge can ignite accumulated vapors particularly during dry weather conditions. Always use proper bonding and grounding procedures.
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

SAFETY DATA SHEET
Klean Strip Paint Thinner

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No data.	No data.	No data.
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	PEL: 500 ppm	TLV: 100 ppm	No data.
25550-14-5	Benzene, Ethylmethyl-	No data.	No data.	No data.
25551-13-7	Benzene, Trimethyl-	No data.	TLV: 25 ppm	No data.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No data.	No data.	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
103-65-1	Benzene, Propyl- {N-Propylbenzene}	No data.	No data.	No data.

Respiratory Equipment (Specify Type): For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Protective Gloves: Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Engineering Controls (Ventilation etc.): Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance Practices: A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid
Appearance and Odor: Water White / Free and Clear
Melting Point: No data.
Boiling Point: 318.00 F - 385.00 F
Autoignition Pt: No data.
Flash Pt: > 100.00 F
Explosive Limits: LEL: 0.5 UEL: 6
Specific Gravity (Water = 1): 0.78
Vapor Pressure (vs. Air or mm Hg): 0.3 MM HG at 68.0 F
Vapor Density (vs. Air = 1): 5 Air = 1
Evaporation Rate: No data.
Solubility in Water: No data.
Solubility Notes: Very slightly soluble in cold water.
Percent Volatile: 100.0 % by weight.
VOC / Volume: 778.0000 G/L

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: No data available.
Incompatibility - Materials To Avoid: Incompatible with strong acids, alkalies, and oxidizers such as liquid chlorine and oxygen.
Hazardous Decomposition Or Byproducts: Decomposition may produce carbon monoxide and carbon dioxide.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Refer to section 2 for acute and chronic effects.
CAS# 25551-13-7:
Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.
Result:
Kidney, Ureter, Bladder: Changes in liver weight.
Endocrine: Changes in thymus weight.
Immunological Including Allergic: Decreased immune response.
- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, 24 H, Mild.
Result:
Kidney, Ureter, Bladder: Changes in liver weight.
Kidney, Ureter, Bladder: Changes in bladder weight.
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.
- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho,

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 7

Printed: 04/20/2015

Revision: 04/20/2015

Supersedes Revision: 09/08/2014

Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 1330-20-7:

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.

Result:

Behavioral: Muscle contraction or spasticity.

Lungs, Thorax, or Respiration:Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	n.a.	n.a.	n.a.	n.a.
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	n.a.	n.a.	n.a.	n.a.
25550-14-5	Benzene, Ethylmethyl-	n.a.	n.a.	n.a.	n.a.
25551-13-7	Benzene, Trimethyl-	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
103-65-1	Benzene, Propyl- {N-Propylbenzene}	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with federal, state, and local regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material, Exempt Combustible Liquid per 49 CFR 173.150(f)

DOT Hazard Class:

UN/NA Number:

Additional Transport Information:

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No	No	No
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	No	No	No
25550-14-5	Benzene, Ethylmethyl-	No	No	No
25551-13-7	Benzene, Trimethyl-	No	No	No
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No	No	Yes
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes
103-65-1	Benzene, Propyl- {N-Propylbenzene}	No	No	No

This material meets the EPA Yes No Acute (immediate) Health Hazard

'Hazard Categories' defined Yes No Chronic (delayed) Health Hazard

for SARA Title III Sections Yes No Fire Hazard

311/312 as indicated: Yes No Sudden Release of Pressure Hazard

Yes No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
25550-14-5	Benzene, Ethylmethyl-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
25551-13-7	Benzene, Trimethyl-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No
103-65-1	Benzene, Propyl- {N-Propylbenzene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 12(b); CA PROP.65: No

SAFETY DATA SHEET

Klean Strip Paint Thinner

Page: 9

Printed: 04/20/2015

Revision: 04/20/2015

Supersedes Revision: 09/08/2014

Regulatory Information Statement: All components of this material are listed on the TSCA Inventory or are exempt.

16. OTHER INFORMATION

Revision Date: 04/20/2015

Preparer Name: W.M. Barr and Company, Inc. (901)775-0100

Additional Information About This Product: No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.