

SAFETY DATA SHEETRevision Date: 01/23/2018Print Date: 11/19/2018Print Date: 11/19/2018SDS Number: R0239085Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor OilValvoline ™ Full Synthetic Advanced SAE 10W-30 Motor OilValvoline ™ Full Synthetic Advanced SAE 10W-30 Motor Oil

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor Oil

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	
1-800-TEAMVAL (1-800-832-6825)	Product Information
, , , , , , , , , , , , , , , , , , ,	1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	5.871
Distillates (Petroleum),	64742-54-7	Asp. Tox. 1; H304	1.254
Hydrotreated Heavy Paraffinic		-	



Valvoline[™] Full Synthetic Advanced SAE 10W-30 Motor Oil

Revision Date: 01/23/2018

Print Date: 11/19/2018 SDS Number: R0239085

Version: 1.4

883452

SECTION 4. FIRST AID MEASURES

SAFETY DATA SHEET

General advice	: No hazards which require special first aid measures.	
If inhaled	 If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. 	
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.	
In case of eye contact	: Remove contact lenses. Protect unharmed eye.	
If swallowed	 Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 	
Most important symptoms and effects, both acute and delayed	 Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological change appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) 	es
Notes to physician	: No hazards which require special first aid measures.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2)
------------------------------	--



Revision Date: 01/23/2018

Version: 1.4

Valvoline[™] Full Synthetic Advanced SAE 10W-30 Motor Oil

883452

SAFETY DATA SHEET

Dry chemical

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide Hydrocarbons nitrogen oxides (NOx)
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters				
Components	CAS-No.	Value type	Control	Basis



		(Form of exposure)	parameters / Permissible concentration	
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.	
Mineral Oil		
Engineering measures	conditions of u exist, provide exhaust) venti guidelines (if a	ventilation should be adequate for normal use. However, if unusual operating conditions sufficient mechanical (general and/or local ilation to maintain exposure below exposure applicable) or below levels that cause known, apparent adverse effects.
Personal protective equipment Respiratory protection :		espiratory protective equipment normally
Eye protection :		under normal conditions of use. Wear splash- oggles if material could be misted or splashed
Skin and body protection :	Wear as appr Safety shoes Wear resistar supplier).	opriate: nt gloves (consult your safety equipment
Hygiene measures	General indus	strial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
Colour	:	amber



Valvoline[™] Full Synthetic Advanced SAE 10W-30 Motor Oil

Page: 5

SAFETY DATA SHEET

Revision Date: 01/23/2018

Print Date: 11/19/2018 SDS Number: R0239085

Version: 1.4

883452

Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 662 °F / 350 °C (1,013.333333 hPa)
Flash point	Calculated Phase Transition Liquid/Gas : > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.1333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8555 g/cm3
Solubility(ies) Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. 70 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY



Revision Date: 01/23/2018

Print Date: 11/19/2018

SDS Number: R0239085 Version: 1.4

Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor Oil

883452

SAFETY DATA SHEET

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

Acute toxicity

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information. Product: Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.



SAFETY DATA SHEET Revision Date: 01/23/2018

Valvoline[™] Full Synthetic Advanced SAE 10W-30 Motor Oil

Version: 1.4

883452

Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Product: No aspiration toxicity classification Components: Mineral Oil: May be fatal if swallowed and enters airways. Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways. **Further information** Product: Remarks: No data available **Carcinogenicity:**

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.
Components:	



SAFETY DATA SHEET	Revision Date: 01/23/2018
	Print Date: 11/19/2018
	SDS Number: R0239085
Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor Oil	Version: 1.4
883452	

Distillates (Petroleum), Hydrotre Toxicity to fish		ted Heavy Paraffinic : LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
Persistence and degradability No data available Bioaccumulative potential No data available Mobility in soil No data available Other adverse effects No data available <u>Product:</u> Additional ecological information	-	No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal	methods
----------	---------

General advice	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	



SAFETY DATA SHEET	Revision Date: 01/23/2018
	Print Date: 11/19/2018
	SDS Number: R0239085
Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor Oil	Version: 1.4
883452	

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION



SAFETY DATA SHEET	Revision Date: 01/23/2018
	Print Date: 11/19/2018
	SDS Number: R0239085
Valvoline [™] Full Synthetic Advanced SAE 10W-30 Motor Oil	Version: 1.4
883452	

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
TOLUENE	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	No SARA Hazards	
SARA 313		This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65		This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.	
The components of this product are reported in the following inventories:			
DSL	•	All components of this product are on the Canadian DSL	
AICS	:	Not in compliance with the inventory	
ENCS	:	On the inventory, or in compliance with the inventory	
KECI	:	On the inventory, or in compliance with the inventory	
IECSC	:	q (quantity restricted)	
PICCS	:	Not in compliance with the inventory	
TSCA	:	On TSCA Inventory	

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information

Revision Date: 01/23/2018

NFPA:

HMIS III:

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 01/23/2018
	Print Date: 11/19/2018
	SDS Number: R0239085
Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor Oil	Version: 1.4
883452	



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"



Revision Date: 01/23/2018

Print Date: 11/19/2018 SDS Number: R0239085

Valvoline™ Full Synthetic Advanced SAE 10W-30 Motor Oil

Version: 1.4

883452

SAFETY DATA SHEET

IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association NIOSH : National Institute for Occupational Safety and Health OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System