

DICK BLICK -- MATTE FIXATIVE;8044-00 -- 8030-00N000401

=====
Product Identification
=====

Product ID:MATTE FIXATIVE;8044-00
MSDS Date:01/01/1985
FSC:8030
NIIN:00N000401
MSDS Number: BCFJR
=== Responsible Party ===
Company Name:DICK BLICK
Address:P O BOX 1267
City:GALESBURG
State:IL
ZIP:61401
Country:US
CAGE:G0856

==== Contractor Identification ===

Company Name:BLICK DICK CO
Address:P O BOX 1267
Box:City:GALESBURG
State:IL
ZIP:61401
Country:US
Phone:309-343-6181
CAGE:06608
Company Name:DICK BLICK
Address:P O BOX 1267
Box:City:GALESBURG
State:IL
ZIP:61401
Country:US
CAGE:G0856

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 35.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 33.0%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000

Fraction by Wt: 32.0%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:MODERATELY TOXIC FROM INH, SKIN
CNTCT/ABSORPTION, EYE CNTCT, INGEST. CNS DEPRSS, ANEMIA, LEUKNPN.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/EYE WASH OR WATER FOR 15 MIN. SKIN: WIPE OFF,
WASH CNTCTD AREA. INH: REMOVE TO FRESH AIR. INGEST: DO NOT INDUCE
VOMIT, GET MD PROMPTLY.

=====
Fire Fighting Measures
=====

Flash Point:3F TCC
Lower Limits:2.6
Upper Limits:12.

=====
Accidental Release Measures
=====

Spill Release Procedures:ADD SOLID ABSORBENT, SCOOP INTO DISPOSAL CART,
HOSE OR WASH DOWN AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID OPEN FLAME OR FIRE, STORE IN
COOL, VENT AREA.
Other Precautions:GROUND EQUIP TO REDUCE ELECTRICAL SPARKING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD SELF-CNTND EQUIP IF VAPOR
EXCEEDS TLV.
Ventilation:MFR REC LOCAL EXH
Eye Protection:SAFETY GLASSES/GOGGLES
Supplemental Safety and Health
AUTOIGNITION TEMP: 1000 F.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:55C
Vapor Density:2.73
Spec Gravity:1.0400
Appearance and Odor:MILD AROMATIC ODOR; WATER WHITE LIQUID
Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
WILL REACT W/STRONG OXIDIZING MATLS
Hazardous Decomposition Products:CO, CO*2

===== Disposal Considerations =====

Waste Disposal Methods: BURY DRUMS IN APPRVD DUMP OR INCINRATE IF IAW
FED, STATE, LOCAL REG.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.